View NSN Online: https://aerobasegroup.com/nsn/6810-00-877-4340

MCB MANUFACTURING CHEMISTS -- DMF -- 6810-00-877-4340

Product ID:DMF MSDS Date:01/01/1985 FSC:6810 NIIN:00-877-4340 **MSDS Number: BFTLN** === Responsible Party === Company Name: MCB MANUFACTURING CHEMISTS Address:2909 HIGHLAND AVE City:CINCINNATI State:OH ZIP:45212-2411 Country:US CAGE:DO964 === Contractor Identification === Company Name: MCB MANUFACTURING CHEMISTS А ddress:2909 HIGHLAND AVE Box:City:CINCINNATI State:OH ZIP:45212-2411 Country:US CAGE:DO964 Company Name: MCB MFG CHEMISTS INC Address:2909 HIGHLAND AVE Box:City:CINCINNATI State:OH ZIP:45212-2411 Country:US CAGE:24150 Ingred Name: DIMETHYLFORMAMIDE CAS:68-12-2

RTECS #:LQ2100000 Fraction by Wt: 100% OSHA PEL:S, 10 PPM ACGIH TLV:S, 10 PPM; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

================== Hazards Identification =====

Effects of Overexposure:IRRITATION TO SKIN,EYES.DAMAGES ORGANS OF BODY,ANOREXIA,NAUSEA,VOMITING
======================================
First Aid:FLUSH WITH WATER.CONSULT DR.
======================================
Flash Point:136 F TCC Lower Limits:2.2 Upper Limits:15.2 Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Ha zard:NONE
======================================
Spill Release Procedures: FLUSH SPILL AREA WITH WATER. ABSORB IF POSSIBLE. AVOID IGNITION SOURCES. PLACE ABSORBED MATERIAL IN CONTAINERS SUITABLE FOR SHIPMENT TO DISPOSAL AREA.
======================================
Handling and Storage Precautions:AVOID EXCESSIVE HEATING Other Precautions:NONE
======== Exposure Controls/Personal Protection ====================================
Respiratory Protect ion:SELF CONTAINED BREATHING GEAR Ventilation:LOCAL RECOMMENDED Protective Gloves:BUTYL RUBBER Eye Protection:SAFETY GLASSES Other Protective Equipment:PROTECTIVE OVERALLS Supplemental Safety and Health
======================================
HCC:F4 Boiling Pt:B.P. Text:307F Vapor Pres:3.7 Spec Gravity:0.9445 Evaporation Rate & amp; Reference:17,BUTYL ACETATE Solubility in Water:HIGH Appearance and Odor:WATER WHITE LIQUID,AMINE SMELL Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES ALUMINUM TRIETHYL Stability Condition to Avoid:UV LIGHT

Waste Disposal Methods: BURNING IN APPROVED INCINERATOR IS BEST METHOD.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in n o manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.