

ALL-STATE WELDING PRODUCTS DIVISION -- ALL-STATE ALUMINUM 5356 -- 3439-00-885-3638  
===== Product Identification =====

Product ID:ALL-STATE ALUMINUM 5356  
MSDS Date:04/16/1991  
FSC:3439  
NIIN:00-885-3638  
MSDS Number: BFTVP  
=== Responsible Party ===  
Company Name:ALL-STATE WELDING PRODUCTS DIVISION  
Address:5112 ALLENDALE ST  
Box:600  
City:TANEYTOWN  
State:MD  
ZIP:21787  
Country:US  
Info Phone Num:301-756-4330

Emergency Phone Num:800-638-1674 OR 717-637-8911  
CAGE:69482  
=== Contractor Identification ===  
Company Name:ALL-STATE PRODUCTS/ DIV OF ESAB GROUP,INC  
Address:5112 ALLENDALE ST  
Box:600  
City:TANEYTOWN  
State:MD  
ZIP:21787  
Country:US  
Phone:1-410-756-4330  
CAGE:69482

===== Composition/Information on Ingredients =====

Ingred Name:SILICON  
CAS:7440-21-3  
RTECS #:VW0400000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:IRON OXIDE  
CAS:1

309-37-1  
RTECS #:NO7400000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:10 MG/M3 (FE)  
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:COPPER (SARA III)  
CAS:7440-50-8  
RTECS #:GL5325000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:0.1MG/M3 FUME/1 DUST  
ACGIH TLV:0.2MG/M3 FUME; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE (SARA III)  
CAS:7439-96-5  
RTECS #:OO9275000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:(C) 5 MG/M3 DUST  
ACGIH TLV:5 MG/M3 DUST 9293

===== Hazards Iden  
tification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:FUMES & GASES CAN BE DANGEROUS TO YOUR  
HEALTH. ACUTE: MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA,  
OR DRYNESS OR IRRITATION OF NOSE, THROAT, OR EYES. CHRONIC: MAY  
LEAD TO SIDEROSIS AND IS BELIEVED TO AFFECT PULMONARY FUNCTIONS.  
ARC RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK CAN KILL.

Expl  
anation of Carcinogenicity:WIRE CONTAINS CHROMIUM FOR WHICH SOME  
EVIDENCE OF CARCINOGENICITY HAS BEEN ESTABLISHED.  
Effects of Overexposure:FUMES & GASES CAN BE DANGEROUS TO YOUR HEALTH.  
ACUTE: MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, OR  
DRYNESS OR IRRITATION OF NOSE, THROAT, OR EYES. CHRONIC: MAY LEAD  
TO SIDEROSIS AND IS BELIEVED TO AFFECT PULMONARY FUNCTIONS. ARC  
RAYS CAN INJURE EYES AND BURN SKIN. ELECTRIC SHOCK CAN KILL.  
Medical Cond Aggravated by Exposure:AGGR

AVATION OF PREEXISTING  
RESPIRATORY OR ALLERGIC CONDITIONS MAY OCCUR IN SOME WORKERS

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. GIVE MOUTH-TO-MOUTH  
RESUSCITATION IF NOT BREATHING. GIVE OXYGEN IF BREATHING IS  
DIFFICULT. GET MEDICAL ATTENTION. EYES: FLUSH WITH RUNNING WATER  
FOR 15 MINUTES WHILE H OLDING EYELID. GET IMMEDIATE MEDICAL  
ATTENTION. SKIN: GET IMMEDIATE MEDICAL ATTENTION FOR SERIOUS BURNS.

=====

===== Fire Fighting Measures =====

Flash Point:NONE  
Autoignition Temp:Autoignition Temp Text:NONE  
Extinguishing Media:USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING  
FIRE.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &  
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING FIRE.  
Unusual Fire/Explosion Hazard:WELDING ARC AND SPARKS CAN IGNITE  
COMBUSTIBLES.

===== Accidental Release Measures =====

Neutralizing Agent:  
NONE

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.  
Other Precautions:READ AND UNDERSTAND THE MANUFACTURER'S INSTRUCTIONS  
AND THE PRECAUTIONARY LABEL ON THIS PRODUCT. SEE AMERICAN NATIONAL  
STANDARD Z-49.1. SAFETY IN WELDING AND CUTTING, PUBLISHED BY THE  
AMERICAN WELDING SOCIETY, POBOX 351040, MIAMI, FL 33135.

===== Exposure Controls/Personal Protection =====

Respiratory Protec  
tion:USE RESPIRABLE FUME RESPIRATOR OR AIR SUPPLIED  
RESPIRATOR WHEN WELDING IN CONFINED SPACE OR WHERE LOCAL EXHAUST OR  
VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV.  
Ventilation:USE ENOUGH VENTILATION AND/OR LOCAL EXHAUST AT THE ARC TO  
KEEP THE FUMES AND GASES BELOW THE TLV'S IN BREATHING ZONE.  
Protective Gloves:WELDERS LEATHER GLOVES  
Eye Protection:HELMET/FACE SHIELD WITH FILTER LENS.  
Other Protective Equipment:WEAR ARM AND SHOULDER PROTECTORS, APRONS,  
HATS, AND DARK SUBSTANTIAL

CLOTHING. USE PROTECTIVE SCREENS IF NECESSARY.

Work Hygienic Practices:MINIMIZE BREATHING FUMES. CLEANSE SKIN THOROUGHLY AFTER USE, BEFORE EATING, AND AT THE END OF WORK PERIOD.

Supplemental Safety and Health

THE COMPOSITION AND QUANTITY OF WELDING FUMES ARE DEPENDENT UPON THE METAL BEING WELDED, THE PROCESS, PROCEDURES AND ELECTRODES USED.

OTHER CONDITIONS WHICH ALSO INFLUENCE THE COMPOSITION AND QUANTITY OF THE FUMES AND GASES TO WHICH WORKERS MAY BE EXPOSED INCLUDE C

OATINGS, (PAINT, GALVANIZE, ETC.) & SOLVENT DEGREASERS.

===== Physical/Chemical Properties =====

HCC:N1

Solubility in Water:NEGLIGIBLE

Appearance and Odor:ALUMINUM WIRE ROLL, 0.047 INCH DIAMETER. NO ODOR.

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:WELDING FUMES

===== Disposal Considerations =====

Waste Disposal Methods:PREVENT WASTE FROM CONTAMINATING SURROUNDING ENVIRONMENT. DISCARD ANY PRODUCT, RESIDUE, DISPOSABLE CONTAINER, OR LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.