

CORONADO PAINT COMPANY, INC -- PAINT, TRAFFIC, WHITE -- 8010-00-900-2938

=====  
Product Identification  
=====

Product ID:PAINT, TRAFFIC, WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-900-2938

MSDS Number: BFVKD

=== Responsible Party ===

Company Name:CORONADO PAINT COMPANY, INC

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

CAGE:33200

=== Contractor Identification =

==

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ALIPHATIC AND AROMATIC HYDROCARBONS

Fraction by Wt: 16.3%

ACGIH TLV:100 PPM

Ingred Name:PIGMENTS

Fraction by Wt: 50.4%

ACGIH TLV:NO HAZARD

Ingred Name:VINYL TOLUENE BUTADIENE

Fraction by Wt: 16.3%

ACGIH TLV:NO HAZARD

=====  
Hazards Identific

ation =====

Effects of Overexposure:SEVERE EYE IRRITATION. DRY SKIN.  
INHALATION-HEADACHE, DIZZINESS, AND NAUSEA.

===== First Aid Measures =====

First Aid:EYE CONTACT-FLUSH WITH WATER. SKIN CONTACT-WASH WITH MILD  
SOAP AND WATER; APPLY SKIN CREAM. INHALATION-REMOVE TO FRESH AIR  
AND CALL A PHYSICIAN; APPLY ARTIFICIAL RESPIRATION, IF NECESSARY.

===== Fire Fighting Measures =====

Flash Point:53 F  
;12 C. SCC  
Lower Limits:0.9  
Upper Limits:7.0  
Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL.  
Fire Fighting Procedures:TREAT AS CLASS B FIRE.  
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH  
AIR.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO  
RETAING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS, FIRE, OR HOT  
METAL SURFACES.

===== Handling and Storage =  
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND OPEN  
FLAME. USE WITH ADEQUATE VENTILATION. AVOID PROLONGED OR REPEATED  
CONTACT WITH SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV  
IS EXCEEDED.  
Ventilation:LOCAL-YES  
Protective Gloves:YES  
Eye Protection:YES  
Other Protective Equipment:EYE BATH AND SAFETY SHOWER.  
Supplemental Safety and Health

=====

=====  
Physical/Chemical Properties  
=====

HCC:F3

Boiling Pt:B.P. Text:133 F,56 C

Vapor Pres:6

Vapor Density:3.7

Spec Gravity:1.32

Evaporation Rate & Reference:1.2 BUAC

Solubility in Water:SLIGHT

Appearance and Odor:WHITE OPAQUE LIQUID, PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume:58.5

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, SPAR

KS, OPEN FLAME OR FIRE.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

=====  
Disposal Considerations  
=====

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied

, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.