

NORRIS PAINT COMPANY -- ZOOM -- 8010-00-901-8081

=====
Product Identification
=====

Product ID:ZOOM

MSDS Date:01/01/1987

FSC:8010

NIIN:00-901-8081

MSDS Number: BFVPH

=== Responsible Party ===

Company Name:NORRIS PAINT COMPANY

Emergency Phone Num:(503) 364-2277

CAGE:JO883

=== Contractor Identification ===

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST NE

Box:2023

C

City:SALEM

State:OR

ZIP:97308

Country:US

Phone:503-364-2277

CAGE:33148

Company Name:NORRIS PAINT COMPANY

Box:2023

CAGE:JO883

=====
Composition/Information on Ingredients
=====

Ingred Name:VINYL ACETATE (SARA III)

CAS:108-05-4

RTECS #:AK0875000

Fraction by Wt: 13.0%

OSHA PEL:10 PPM/15 STEL

ACGIH TLV:10 PPM/15,A3 STEL;93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2.3%

OSHA PEL:C 50 PPM

ACGIH

TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 13.3%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT OTHERWISE REGULATED)

CAS:1302-76-7

RTECS #:BD1450000

Fraction by Wt: 25.7%

OSHA PEL:15 MG/M3 TOTAL DUST

ACGIH TLV:10 MG/M3 TDUST;8990

Ingred Name:PHENYLMERCURIC ACETATE (SARA III)

CAS:62-38-4

RTECS #:OV6475000

Fraction by Wt:

0.1%

OSHA PEL:0.1 MG HG/M3;CEIL;S

ACGIH TLV:0.01 MG HG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:VAPOR MAY BE IRRIT TO EYES, SKIN, MAY CAUSE SYMPTOMS OF HEADACHE, NAUSEA IN POORLY VENTIL AREAS.

=====
===== First Aid Measures =====

First Aid:SKIN CONTACT:WASH THOROUGHLY W/SOAP & WATER.EYES:FLUSH W/PLENTY OF WATER FOR 15 MIN. CALL PHYSICIAN. IF EXPOSED TO LARGE AMOUNTS OF SPRAY MIST REMOVE TO FRESH AIR. INGEST:INDUCE VOMITING. CALL MD.

=====
===== Fire Fighting Measures =====

Flash Point:NON FLAMMABLE

Fire Fighting Procedures:N/A ACCD TO MFR

=====
===== Accidental Release Measures =====

Spill Release Procedures:ABSORB SPILL,FLUSH W/LARGE AMOUNTS OF WATER IMMED. TRANSFER TO CONTAINERS FOR RECOVERY OR DISPOSAL. DO NOT FLUSH DOWN SEWER SYSTEM.

=====
===== Handling and

Storage =====

Handling and Storage Precautions:KEEP MATERIAL FROM FREEZING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR WHEN SPRAYING
PAINT

Ventilation:ADEQUATE VENTILATION

Protective Gloves:NOT NEC REQD

Eye Protection:SPLASH PROOF SAFETY GOG

Other Protective Equipment:EYE WASH EQUIPMENT

Supplemental Safety and Health

ADDITIONAL INGREDIENTS:WATER,43.7%; CELLULOSE, 1.0%; SURFACTANTS, 1.0%

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F

Vapor Pres:024

Vapor Density:>1.0

Spec Gravity:1.4100

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:COMPLETE

Appearance and Odor:CONSISTENCY OF CREAM, SLIGHT PAINT ODOR

Percent Volatiles by Volume:49.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OIL & OIL BASE MATERIALS, PETROLEUM DISTILLATES,STRONG ACIDS

S

Stability Condition to Avoid:EXTREME HEAT OVER 200F

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM DISPOSE IN LANDFILL IAW FED, STATE &
LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.