

BURDICK AND JACKSON DIV OF BAXTER HEALTHCARE CORP. -- NORMAL HEXANE --  
6810-00-902-3562

=====  
Product Identification  
=====

Product ID:NORMAL HEXANE

MSDS Date:01/01/1985

FSC:6810

NIIN:00-902-3562

MSDS Number: BFVQH

=== Responsible Party ===

Company Name:BURDICK AND JACKSON DIV OF BAXTER HEALTHCARE CORP.

Address:1953 S HARVEY STREET

City:MUSKEGON

State:MI

ZIP:49442-6101

Country:US

Info Phone Num:616

-726-3171

Emergency Phone Num:616-726-3171, CHEMTREC 800-424-9300

CAGE:2H215

=== Contractor Identification ===

Company Name:HONEYWELL, BURDICK AND JACKSON

Address:1953 S HARVEY STREET

Box:City:MUSKEGON

State:MI

ZIP:49442-6101

Country:US

Phone:800-368-0050/800-707-4555

CAGE:2H215

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:M

ETHYLCYCLOPENTANE  
CAS:96-37-7  
RTECS #:GY4640000  
Fraction by Wt: 10%  
ACGIH TLV:500 PPM (MFR)

=====  
===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN: IRRITATION. VAPOR:  
DIZZY,NAUSEA,EXHILIRATION,MUSCULAR INCOORD,STUPOR,UNCONSCIOUSNESS.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MIN. SKIN: WASH WITH SOAP &  
WATER,APPLY EMMOLIENT CREAM. INHALATION: REMOVE FROM EXPOSURE,GIVE  
ARTI  
FICAL RESPIRATION: DO NOT INDUCE VOMITING,GET MEDICAL  
ASSISTANCE.

=====  
===== Fire Fighting Measures =====

Flash Point:-10F/-23C )TCT)  
Lower Limits:1.2  
Upper Limits:7.7  
Extinguishing Media:DRY CHEMICAL,CO\*2  
Fire Fighting Procedures:WATER SPRAY TO COOL EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:WTER MAY BE INEFFECTIVE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SECURE IGNITION SOURCES,ABSORB IN EARTH OR  
SAWDUST. WEAR APPROVED RESPIRATORY DEVICE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL WELL VENTILATED SPACE.  
Other Precautions:USE A SELF-CONTAINED BREATHING APPARATUS IF ENTRY  
INTO A STOREAGE TANK OR VESSEL IS REQUIRED.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN.  
Ventilation:MECHANICAL/GENERAL  
Pr

Protective Gloves:NEOPRENE  
Eye Protection:PROTECTIVE GOGGLES  
Supplemental Safety and Health  
PHILLIPS PETROLEUM CO MFR'S RAW MATERIAL,BURDICK & JACKSON LAB REFINES  
TO DESIRED PCT,SPEC & GRADE. CONTAINER SIZE: 250 GM BOTTLE

===== Physical/Chemical Properties =====

HCC:F2  
Boiling Pt:B.P. Text:152F/66C  
Vapor Pres:130  
Vapor Density:3.0  
Spec Gravity:0.67  
Evaporation Rate & Reference:0.3 (ETHYL ETHER)  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:WATER-WHITE NON  
-VISCIOUS LIQUID - MILD ODOR.  
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:CONTROLLED BURNING AT A SAFE LOCATION. COMPLY  
WITH LOCAL,STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.