View NSN Online: https://aerobasegroup.com/nsn/9150-00-903-6431

NORTON CHEMPLAST DBA NORTON PERFORMANCE PLASTICS -- FLUOROGLIDE FB -- 9150-00-903-6431

========== Product Identification ==========

Product ID:FLUOROGLIDE FB
MSDS Date:01/01/1987
FSC:9150
NIIN:00-903-6431
MSDS Number: BFVST
=== Responsible Party ===
Company Name:NORTON CHEMPLAST DBA NORTON PERFORMANCE PLASTICS
Address:150 DEY RD
City:WAYNE
State:NJ
ZIP:07470-4670
Country:US
Info Phone Num:201-696-4700
Emer
gency Phone Num:201-696-4700
CAGE:18632
=== Contractor Identification ===
Company Name:NORTON PERFORMANCE PLASTICS CORP.
Address:150 DEY RD
Box:City:WAYNE
State:NJ
ZIP:07470-4670
Country:US
Phone:973-696-4700
Contract Num:SP0450-00-M-C243
CAGE:18632
Company Name:SAINT GOBAIN DESJONQUERES SA
Address:LES MIROIRS LA DEFENSE 3
Box:City:COURBEVOIE F-92400, FRANCE
Country:FR
Phone:0-14-762-3330
CAGE:F1926

========== Composition/Information on Ingredients ==========

Ingred Name:ACRYLIC COPOLY

MER
Fraction by Wt: 1-5%
Other REC Limits:NONE SPECIFIED

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 85-90%
Other REC Limits:NONE SPECIFIED
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:1,1,2-TRICHLORO-1,2,2-TRIFLUOROETHANE (FREON 113) (SARA III)
CAS:76-13-1
RTECS #:KJ4000000
Other REC Limits:NONE SPECIFIED
OSHA PEL:1000PPM/1250STEL

ACGIH TLV:1000PPM/1250STEL9192
Ozone Depleting Chemical:1

Ingred Name:TETRAFLUOROETHYLENE, INHIBITED
CAS:116-14-3
RTECS #:KX4000000
Fraction by Wt: 15-20%
Other REC Limits:NONE SPECIFIED

Ingred Name:CARBON DIOXIDE
CAS:124-38-9
RTECS #:FF6400000
Fraction by Wt: 3%
Other REC Limits:NONE SPECIFIED
OSHA PEL:5000 PPM
ACGIH TLV:5000PPM/30000STEL;93

========== Hazards Identification ==========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicit

y:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MILD INTOXICATION OR ANAESTHESIA.
Explanation of Carcinogenicity:NOT LISTED AS A CARCINOGEN BY NTP, IARC OR OSHA
Effects of Overexposure:INTIXICATION, LOSS OF COORDINATION.

========== First Aid Measures ==========

First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. SKIN CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTO
MS PERSIST. INGESTION:DO
NO T INDUCE VOMITING, GET MEDICAL HELP IMMEDIATELY.

========== Fire Fighting Measures ==========

Flash Point Method:COC
Flash Point:NONE
Lower Limits:6.0%
Upper Limits:16.7%
Extinguishing Media:USE WATER, FOG, CARBON DIOXIDE, OR DRY CHEMICAL.
Fire Fighting Procedures:USE POSITIVE PRESSURE, SELF-CONTAINED RESPIRATORY EQUIPMENT. MUST WEAR PROTECTIVE GEAR. MOVE CONTAINER FROM FIRE AREA IF POSSIBLE.DO NOT SCATTER SPILLAGE.
Unusual Fire/E
xplosion Hazard:CONTENTS UNDER PRESSURE, HEAT MAY CAUSE BURSTING OF CAN, COLD WATER SPRAY MAY REDUCE VAPOR PRESSURE IN CONTAINER. THERMAL DECOMPOSITION MAY OCCUR.

========== Accidental Release Measures ==========

Spill Release Procedures:PICK UP CANS. VENTILATE AREA IF CANS ARE LEAKING.
Neutralizing Agent:NONE

========== Handling and Storage ==========

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE IN A DRY PLACE. KEEP CO
NTAINER TIGHTLY SEALED, PROTECT FROM EXCESSIVE HEAT AND OPEN FLAMES.
Other Precautions:VOID CONTAMINATING TABACCO PRODUCTS.

========== Exposure Controls/Personal Protection ==========

Respiratory Protection:NO REQUIRED
Ventilation:LOCAL
Protective Gloves:NONE
Eye Protection:GOGGLES
Other Protective Equipment:EYE WASH
Work Hygienic Practices:DO NOT SMOKE, EAT OR DRINK WHEN USING CANS.
Supplemental Safety and Health
NONE

========== Physical/Chemical Properties ==========

======

HCC:V2
Boiling Pt:B.P. Text:140F,60C
Vapor Pres:120 @20C
Spec Gravity:1.2
Solubility in Water:NEGLIBLE
Appearance and Odor:TRANSLUCENT OR OPAQUE LIQUID, ETHEREAL ODOR.
Percent Volatiles by Volume:95

========== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES
ALUMINUM AND ITS ALLOYS.
Stability Condition to Avoid:OPEN FLAME, WELDING ARC, OR OTHER HIGH
TEMPERATURE SOURCES WHICH INDUCE THERMAL DECOMPOSITION.
Hazardous Decomposition Pro
ducts:HYDROGEN CHLORIDE, HYDROGEN FLUORIDES,
ACRYLIC MONOMER, AND POSSIBLE TRACES OF PHOSGENE.

========== Disposal Considerations ==========

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.