

EASTMAN KODAK COMPANY -- 101 0032 INDUSTREX MANUAL DEVL & REPL,PT A( --  
6750-00-905-5123

===== Product Identification =====

Product ID:101 0032 INDUSTREX MANUAL DEVL & REPL,PT A(

MSDS Date:07/01/1992

FSC:6750

NIIN:00-905-5123

Kit Part:Y

MSDS Number: BFVWX

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Nu

m:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: 1-5%

Other REC Limits:NONE SPECIFIED BY M.

OSHA PEL:C, 2 MG/M3

ACG

IH TLV:C 2 MG/M3; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:HYDROQUINONE (SARA III)  
CAS:123-31-9  
RTECS #:MX3500000  
Fraction by Wt: 4.0%  
Other REC Limits:NONE SPECIFIED BY M.  
OSHA PEL:2 MG/M3  
ACGIH TLV:2 MG/M3; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:P-METHYLAMINOPHENOL SULFATE;  
CAS:55-55-1  
RTECS #:SL8650000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE NORMALLY REQUI.

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 65-70%

Ingred Name:POTASSIUM SULFI  
TE  
CAS:10117-38-1  
Fraction by Wt: 10-15%  
Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM SULFITE  
CAS:7757-83-7  
RTECS #:WE2150000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL, LD50 (RAT) = 2-5 ML/KG  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-SKIN:IRRITATION. EYE:IRRITATION,  
BURNS. INHA

LATION:LOW HAZARD. INGESTION:HARMFUL, MAY CAUSE BURNS OF  
INTESTINAL TRACT. CHRONIC-SKIN ALLERGIC REACTION.  
Effects of Overexposure:EYES:IRRITATION, REDNESS, BURNS.  
SKIN:IRRITATION. INGESTION:STOMACHACHE, DIARRHEA.  
Medical Cond Aggravated by Exposure:SKIN DISORDERS.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR. EYE CONTACT:FLUSH WITH WATER  
FOR 15 MINUTES. GET MEDICAL ATTENTION IMMEDIATELY. SKIN  
CONTACT:WASH WITH SO  
AP AND WATER. GET MED ATTENTION IF SYMPTOMS  
PERSIST. INGESTION: DO NOT INDUCE VOMITING. DRINK 1-2 GLASSES OF  
WATER, GET MEDICAL HELP IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:NOT COMBUSTIBLE:USE MEDIA SUITABLE FOR ADJACENT  
FIRE.  
Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR PROTECTIVE CLOTHING  
AND SELF-CONTAINED BREATHING APPARATUS.  
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
  
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS;CONTNRS MAY RUPTURE  
IN HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR SUITABLE PROTECTIVE EQUIP. AVOID CONTACT  
W/LIQ; ABSORB WITH INERT MATERIAL AND SAVE IN A DISPOSAL CONTAINER.  
FLUSH RESIDUE TO AN ACID FREE SEWER WITH LARGE AMTS OF WATER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED  
  
AREA; PROTECT FROM PHYSICAL DAMAGE & AVOID CONTACT. KEEP CONTAINERS  
TIGHTLY CLOSED. PREVENT SKIN CONTACT.  
Other Precautions:REMOVE & WASH CONTAMINATED CLOTHING. MAINTAIN STRICT  
HYGIENE. USE OF NON-ALKALINE(ACID) TYPE HAND CLEANER REDUCES RISK  
OF ALLERGIC SKIN REACTION. DO NOT REUSE EMPTY CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED  
Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED  
Pr

Protective Gloves:IMPERVIOUS/RUBBER

Eye Protection:SAFETY/CHEM GOGGLES.

Other Protective Equipment:FULL WORK CLOTHING; FACE SHIELD WHEN USING/  
MIXING PRODUCT.

Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH  
THIS PRODUCT.

Supplemental Safety and Health

THIS IS PART A OF 2 PART KIT, THIS ENTRY DESCRIBES NEW FORMULATION AND  
NEW CAT #, FOR OLD CAT#, SEE P/N IND A, THIS NSN, APPROX PH 12.0.  
THIS CAT # IS FOR MAKING 1 GALLON.

===== Physical/Chemical P  
roperties =====

HCC:B3

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18 MMHG

Vapor Density:0.60

Spec Gravity:1.29

pH:12.0

Solubility in Water:COMPLETE

Appearance and Odor:LIGHT BROWN LIQUID;ODORLESS

Percent Volatiles by Volume:65%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MINERAL ACIDS

Stability Condition to Avoid:EXCESSIV HEAT

Hazardous Decomposition Products:SULFUR DIOXIDE

===== Disposal Consid  
erations =====

Waste Disposal Methods:DISPOSE IN FULL ACCORDANCE WITH ALL APPLICABLE  
INTERNATIONAL, FEDERAL, STATE & LOCAL REGULATIONS. MFG SUGGESTS  
FLUSH TO SEWER W EXCESS H2O.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all lia

bility for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.