

ESSEX CHEMICAL CORP, SPECIALTY CHEM. DIV -- PRO-SEAL 776 PRIMER -- 8040-00-919-6797
===== Product Identification =====

Product ID:PRO-SEAL 776 PRIMER

MSDS Date:01/01/1985

FSC:8040

NIIN:00-919-6797

MSDS Number: BFWJR

=== Responsible Party ===

Company Name:ESSEX CHEMICAL CORP, SPECIALTY CHEM. DIV

Address:19451 SUSANA RD

City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:83527

=== Contractor Ident

ification ===

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Phone:310-537-7600

CAGE:83527

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 25%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification ===

=====

Effects of Overexposure:IRRITANT TO MUCOUS SURFACES. NARCOTIC EFFECT.

===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR. WASH THOROUGHLY AFTER CONTACT. GIVE EMETIC IF INGESTED. CONSULT MD.

===== Fire Fighting Measures =====

Flash Point:28F,CC
Lower Limits:1.8
Upper Limits:9.50
Extinguishing Media:CO*2, FOAM, DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:FLAMMA
BLE SOLVENT, RED LABEL

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP W/ SAWDUST OR SWEEPING COMPOUND

===== Handling and Storage =====

Handling and Storage Precautions:AVOID SPARKS & OPEN FLAME. STORE BELOW 80F IN CLSD CONTAINER
Other Precautions:RED LABEL MATERIAL. HIGHLY FLAMMABLE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPRVD ABS ORPTIVE MASK IN CONFINED AREAS(MFG)
Ventilation:LOC EXHST REQUIRED, POSITIVE AIR FLOW (MFR RECM)
Protective Gloves:NEOPRENE
Eye Protection:SAFETY GLASSES
Supplemental Safety and Health
PART A OF A TWO PART PRODUCT.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175F (MEK)
Vapor Pres:71
Vapor Density:2.4
Spec Gravity:1.0
Evaporation Rate & Reference:4.0 (N-BUTYL
Solubility in Water:APPRECIABLE
Appearance and Odor:YELLOW SLURRY, KETONE ODOR
Perc

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING & REDUCING AGENTS

Stability Condition to Avoid:EXPOSURE TO SPARKS OR FLAME

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the

Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.