

FARWEST PAINT MANUFACTURING CO -- TT-S-708A, DARK REDWOOD, SEMI-TRANSPARENT --
8010-00-926-9129

===== Product Identification =====

Product ID:TT-S-708A, DARK REDWOOD, SEMI-TRANSPARENT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-926-9129

MSDS Number: BFWYD

=== Responsible Party ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

CAGE:2F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 S 133RD ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:2F266

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 3.7%

OSHA PEL:10 MG/M3

(FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:VEHICLE(SEE SUPPLEMENTAL DATA FOR SPECIFIC VEHICLE COMPONENTS)
Fraction by Wt: 65.2%

Ingred Name:SUSPENDING AGENTS
Fraction by Wt: 0.32%

Ingred Name:PARAFFIN SOLVENTS (INCLUDING NAPHTHENES)
Fraction by Wt: 25.4%
ACGIH TLV:200 PPM-MFG

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 2.21%
OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexpo
sure:SKIN:DRY&CRACKED.INHAL:HEADACHE,DIZ,LOSS OF
COORDINATN.ASPIRATN OF LIQ:LEAD TO CHEM.PNEUMONITIS.

=====
First Aid Measures
=====

First Aid:EYES:IMMED FLUSH W/WATER AT LEAST 15 MIN CALL MD IF NEC.
SKIN:WASH THOROUGHLY W/SOAP & WATER. INGEST:DO NOT INDUCE VOMITING,
CALL MD IMMED. INHAL:MOVE TO FRESH AIR. CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:100F TCC
Lower Limits:1.0
Upper Limits:6.0
Exstin
guishing Media:CO*2, DRY CHEMICAL, FOAM, WATER SPRAY.
Fire Fighting Procedures:CONFINED AREAS-USE PROTECTIVE
EQUIP,INCL.BREATHING APPARATUS

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION IN VICINITY
OF SPILL OR RELEASED VAPORS. CLEAN UP AS SOON AS POSSIBLE. ABSORB
LARGE SPILLS W/DIATOMACEOUS EARTH OR ABSORBENT CLAY.

=====
Handling and Storage
=====

Handling and Stora

ge Precautions:KEEP AWAY FROM HEAT OR OPEN FLAME. USE
IN VENTILATED AREA. MFG SUGGESTS TLV OF 200 PPM FOR DAILY 8 HOUR
EXPOSURE.

Other Precautions:VAPOR PRESS:5MMHG@77F. PERCENT VOLATILE BY
VOLUME:99T.DOT CLASSIFICATION:FLAMMABLE LIQUID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR CONC.>TLV USE APPR. ORG. VAPOR RESP.OR
SELF-CONTAINED BRTHNG EQP

Ventilation:KEEP VAPOR & MIST BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection

:CHEM-SFTY GOGGLES

Other Protective Equipment:EYE WASH STAND. GLOVES MAY BE NEOPRENE OR
RUBBER.

Supplemental Safety and Health

NIGHT EMERGENCY#(206)241-1619.VEHICLE CONTAINS:LINSEED OIL(42.1%,OF
PRODUCT);PARAFFIN WAX(1.7 TO 2.0%);PENTACHLOROPHENOL(3.3%),TLV-SKIN
0.5MG/CUM;VOLATILE THINNER (18.2%).

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:313 TO 404F

Vapor Density:4.9

Spec Gravity:0.801

Evaporation Rate & Reference:0.13 BUT

YL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:COLORED LIQUID.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MAY REACT W/STRONG OXIDIZING MATERIALS.

Hazardous Decomposition Products:NORMAL COMBUTN:CO*2 & H*2O

VAPOR,INCOMPL.COMBUSTN:CO

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN APPROVED DUMPING AREA.

Disclaimer (provided with this information by t

he compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.