

NONFLUID OIL CORP -- G-60/EPZ:LUBRICATING GREASE -- 9150-00-929-7946

=====  
Product Identification  
=====

Product ID:G-60/EPZ:LUBRICATING GREASE

MSDS Date:09/01/1987

FSC:9150

NIIN:00-929-7946

MSDS Number: BFXCQ

=== Responsible Party ===

Company Name:NONFLUID OIL CORP

Address:298 DELANCY STREET

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Info Phone Num:201-344-3451

Emergency Phone Num:201-344-345

1

CAGE:76736

=== Contractor Identification ===

Company Name:NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LUBRICATING GREASE

Other REC Limits:5MG/CUM,AS OIL MIST

Ingred Name:OTHER COMPONENTS(NOT SPECIFIED)

=====  
Hazards Identification  
=====

Routes of Entry: Inhal

ation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:MILD IRRITATION OF EYES AND SKIN;IRRITATION OF MUCOUS MEMBRANE OR RESPIRATORY TRACT IN CASE OF EXPOSURE TO OIL MIST. CHRONIC:DEFATTING OF SKIN OR DERMATITIS.

Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====  
===== First Aid Measures =====

First Aid:SKIN & EYES:FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES:SEEK MEDIC

AL HELP. INHALATION:REMOVE TO FRESH AIR.

INGESTION:SEEK MEDICAL ASSISTANCE IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>400F/204C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CO\*2,DRY CHEMICAL,FOAM,WATER FOG

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:NONE NOTED

=====  
===== Accidental Release Measures =====

Spill Release

Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL

IGNITION SOURCES;RECOVER FREE PRODUCT;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED

AREA;KEEP AWAY FROM HEAT,OPEN FLAMES.WASH THOROUGHLY AFTER EACH USE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT REQUIR

ED;USE NIOSH/MSHA APPROVED

RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV OR AN ADEQUATE VENTILATION.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:APRON,EYE-WASH FOUNTAIN

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;WASH THOROUGHLY.DO NOT EAT,DRINK OR SMOKE IN WORK AREA.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Bo

iling Pt:B.P. Text:600F/316C

Melt/Freeze Pt:M.P/F.P Text:NEGLIGIBLE

Vapor Pres:10

Spec Gravity:0.90

Evaporation Rate & Reference: