

AMERON INDUSTRIAL COATING DIVISION -- 794-430 -- 8010-00-935-7071

=====  
Product Identification  
=====

Product ID:794-430

MSDS Date:01/01/1987

FSC:8010

NIIN:00-935-7071

MSDS Number: BFXVM

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATING DIVISION

Emergency Phone Num:316-733-1361

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201

N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 3.3%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 22.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000

LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 15.5%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:CYCLOHEXANONE (SARA III)  
CAS:108-94-1  
RTECS #:GW1050000  
Fraction by Wt: 19.2%  
OSHA PEL:S, 50 PPM  
ACGIH TLV:S, 25 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Fraction by Wt: 10.3%  
OSHA PEL:0.05 MG/M3;1910.1025  
ACGI  
H TLV:0.15 MG/M3;DUST 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

=====  
===== Hazards Identification =====

Effects of Overexposure:INHALE:ANESTHETIC,IRRITATION OF RESPIRATORY  
TRACT,ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY

=====  
===== First Aid Measures =====

First Aid:INCASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER  
WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH  
AIR.CALL A PHYSICIAN IF SYMPT

OMS PERSIST.

=====  
===== Fire Fighting Measures =====

Flash Point:45F,7C TCC

Lower Limits:1.0

Extinguishing Media:CARBON DIOXIDE/DRY CHEMICAL-SMALL;POLYMER  
FOAM-LARGE FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARTUS AVAILABLE  
FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD UP

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE AL

L SOURCES OF IGNITION(FLAMES,HOT

SURFACES,AND ELECTRICAL,STATIC,OR FRICTIONAL SPARKS)AVOID BREATHING  
VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING  
TOOLS

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA  
CLASS ONE FLAMMABLE (OR COMBUSTIBLE)LIQUID

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOUL  
D BE GROUNDED

WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME  
CUT,BRAZE,OR WELD COATED MATERIAL WITHOUT VENTILATION

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER  
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV/LEL SAFETY& WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CON  
TACT TO

CONTAMINATED CLOTHING

Supplemental Safety and Health

BP 79-153C.EFFTS. OF OVEREXPOSURE-HEADACHE,DIZZINESS,ETC. OR  
COMA.PRIMARY IRRITATION FOR SKIN OR EYE CONTACT.

=====  
===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:174-308F

Evaporation Rate & Reference:< ETHER

Percent Volatiles by Volume:70.0

=====  
===== Stability and Reactivity Data =====

Stability Condition to Avoid:FIRES,HEAT,AND HOT SURFACES

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE,AND  
FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY.DO NOT  
INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.