

ALOX CORP -- ALOX 2028C -- 8030-00-938-1947

=====
===== Product Identification =====

Product ID:ALOX 2028C
MSDS Date:01/01/1987
FSC:8030
NIIN:00-938-1947
MSDS Number: BFYGR
=== Responsible Party ===
Company Name:ALOX CORP
Address:3943 BUFFALO AVE
Box:517
City:NIAGARA FALLS
State:NY
ZIP:14302
Country:US
Info Phone Num:716-282-1295
Emergency Phone Num:716-282-1295
CAGE:60773

=== Contractor Identification
===

Company Name:ALOX CORP
Address:3943 BUFFALO AVE
Box:517
City:NIAGARA FALLS
State:NY
ZIP:14302
Country:US
Phone:716-282-1295
CAGE:60773

=====
===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC MINERAL SPIRITS, CAS# 64742-88-7
Fraction by Wt: 50%
ACGIH TLV:100 PPM
Fraction by Wt: 50%

Ingred Name:**NEUTRALIZED W/BARIUM, THEN BLENDED W/BA SULFONATE &
MINERAL SPIRITS. BARIUM COMPOUNDS (4% IN NON-MINERAL SPIRITS. ***
RTECS #:9999999ZZ
Other REC Limits:NONE

SPECIFIED

Ingred Name:***PORTION, 2% IN ALOX 2028C) ARE NOT WATER SOLUBLE).

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Effects of Overexposure:INHAL:NAUS,DIZZ,NOSE,THROAT IRRIT,WATERING EYES.INGEST:IRRIT,VOMIT,DIARR,NAUS.SKIN:HOT MATRL BURNS.

=====
===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR,TREAT SYMPTOM.GIVE O*2 IF BREATH IMPAIRED.EYE:FLUSH W/ WATER F OR AT LEAST 15 MIN.CALL MD.SKIN:WASH W/ SOAP & WATER.TREAT BURNS FROM HOT MATRL AS THERMAL BURNS.INGEST:DO NOT I NDUCE VOMIT.CALL MD.

=====
===== Fire Fighting Measures =====

Flash Point:142F,61C TCC

Extinguishing Media:CO*2,DRY CHEMICAL,WATER FOG

Fire Fighting Procedures:DO NOT USE H*2O EXCEPT AS FOG OR TO COOL CONTNR,FLUSH SPILL

Unusual Fire/Explosion Hazard:WATER STREAMS ON BURNING MATERIAL MAY SPREAD FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:ATTEMPT TO RECOVER.KEEP PETROLEUM PRODUCTS OUT OF STREAMS AND WATERWAYS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID PRLG/RPTD CONTACT.KEEP CONTAINERS CLOSED WHEN NOT IN USE.WASH BEFORE EATING,SMOKING OR USING TOILET.WASH SATURATED CLOTHING BEFORE REUSE.

Other Precautions:IF INGESTION & VOMITING OCCURS,MONITOR PATIENT FOR 48 HOURS FOR BREATHING DIFFICULTIES.

==

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST PREFERRED

Protective Gloves:OIL IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS NEEDED TO PROTECT AGAINST HOT
PROD,RPTD/PRLG CONTACT.

Supplemental Safety and Health

MSDS PREP:86197.SPEC TYPE 2 AND CLASS 2.

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text:>302F,>150C

Vapor Pres:1

Spec Gravity:0.86

Evaporation Rate & Reference

: