

FILTRON CO. -- FSC-W25B2 -- 5915-00-944-7670

===== Product Identification =====

Product ID:FSC-W25B2

MSDS Date:01/01/1985

FSC:5915

NIIN:00-944-7670

MSDS Number: BFYPH

=== Responsible Party ===

Company Name:FILTRON CO.

Emergency Phone Num:516 752 1144

CAGE:MO334

=== Contractor Identification ===

Company Name:FILTRON CO INC

Address:148 SWEET HOLLOW RD

Box:City:OLD BETHPAGE

State:NY

ZIP:11804-1315

Co

Country:US

Phone:914-699-2000

CAGE:81831

Company Name:FILTRON CO.

CAGE:MO334

===== Composition/Information on Ingredients =====

Ingred Name:POLYCHLORINATED BIPHENYLS (PCBS) (SARA III)

CAS:1336-36-3

RTECS #:TQ1350000

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

===== Hazards Identification =====

Effects of Overexposure:MAY CAUSE IRRITATION TO EYES, NOSE AND THROAT
AND A SKIN RASH MAY INJURE LIVER

===== First Aid Measures =====

=====

First Aid:EYES:FLUSH W/WATER IMMED. SKIN:WASH W/SOAP IMMED. INHAL REMOVE TO FRESH AIR, RESPIR. AS NEEDED INGEST:MEDICAL ATTN. GIVE LARGE QTY OF WATER. INDUCE VOMITING, BUT DO NOT MAKE UNCONSCIOUS PERSON VOMIT.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL,CARBON DIOXIDE
Fire Fighting Procedures:DO NOT USE WATER, WEAR RESPIRATOR AND PROTECTIVE CLOTHING
Unusual Fire/Explosion Hazard:TOXIC GASES AND VA
PORS I.E HYDROGEN
CHLORIDE CARBON MONOXIDE

===== Accidental Release Measures =====

Spill Release Procedures:PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE RESTRICTED. REMOVE ALL IGNITION SOURCES. VENTILATE SPILL AREA. COLLECT FOR RECLAMATION OR ABSORB W/DRY POWDERED CLAY OR SAND

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE MUST FOLLOW RCRA REQUIREMENTS
Other Precautions:CHL
ORODIPHENYL WILL ATTACK SOME FORMS OF PLASTIC,RUBBER AND COATINGS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SUPPLIED AIR W/FULL FACEPIECE, HELMET OR HOOD
Ventilation:LOCAL EXHAUST
Protective Gloves:IMPERV GLOVES
Eye Protection:GOGGLES, FACE SHIELD
Other Protective Equipment:FULL CLOTHING TO PREVENT SKIN CONTACT
Supplemental Safety and Health
OVEREXPOSURE MAY CAUSE FORMATION OF CYSTS, STILLBIRTHS. EYES,NOSE, AND THROAT IRRITATION.

=====

===== Physical/Chemical Properties =====

HCC:Z3

Appearance and Odor:PALE YELLOW VISCOUS LIQUID W/HYDROCARBON ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS MAY CAUSE FIRES AND EXPLOSIONS

Stability Condition to Avoid:HEAT

Hazardous Decomposition Products:TOXIC GASES AND VAPORS I.E. HYDROGEN
CHLORIDE CARBON MONOXID

===== Disposal Considerations =====

Waste Disposal Methods:ABSORBED MATERIAL DISPOSED OF IN SANITARY
LANDFILL. CONTAMINATED CLOTHS SHOULD BE PLACED IN CLOSED CONTAINER
TO DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.