

CONTINENTAL CHEM CORP -- PURGING FLUID -- 6850-00-965-2356

=====  
Product Identification  
=====

Product ID: PURGING FLUID

MSDS Date: 01/01/1985

FSC: 6850

NIIN: 00-965-2356

MSDS Number: BFZQV

=== Responsible Party ===

Company Name: CONTINENTAL CHEM CORP

Emergency Phone Num: 812-235-8035

CAGE: 23894

=== Contractor Identification ===

Company Name: CONTINENTAL CHEM CORP

Address: 1330 BEECH STREET

Box: City: TERRE

HAUTE

State: IN

Country: US

CAGE: 23894

=====  
Composition/Information on Ingredients  
=====

Ingred Name: PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS: 8002-05-9

RTECS #: SE7449000

OSHA PEL: 400 PPM

ACGIH TLV: 400 PPM; 8990

=====  
Hazards Identification  
=====

Effects of Overexposure: MINOR IRRIT TO SENSITIVE SKIN. AVOID BRTHNG  
MISTS. PROD GENERALLY NOT CONSIDERED TOXIC.

=====  
First Aid Measures  
=====

First Aid: EXTERNAL: WIPE FROM EXPOSED AREA, THEN WASH W/SOAP & WATER.

INTERN: DO NOT INDUCE VOMIT, ADMINISTER 2OZ VEG OIL. CONSULT MD.

=====  
Fire Fighting Measures  
=====

Flash Point: 240F PMCC

Extinguishing Media: DRY CHEM, CO\*2

Unusual Fire/Explosion Hazard: KEEP FROM HEAT & OPEN FLAME

=====  
Accidental Release Measures  
=====

Spill Release Procedures: NORMAL PRECAUTIONARY MEASURES FOR HANDLING  
LUBRICATING OILS ARE SATISFACTOR

Y. REMOVE SPARKS, FLAMES, HOT SURFS. COLLECT ON ABSORBENTS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:AVOID TEMPS ABOVE 140F FOR PROLONGED PERIODS. AVOID OR CONTAIN OIL MISTS.

Other Precautions:PERSONS EXPOSED TO OIL MISTS SHOULD WEAR APPRVD BRTNG DEVICES

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:SELECT ACCORDING TO AMERICAN NATL STD PRACTICES FOR RESP PROT

Protective

Gloves:OIL RESIST

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

TYPICAL POUR POINT OF ITEM IS -100F. RESP PROT SELECTED ACCORDING TO AMERICAN NATL STANDARD PRACTICES FOR RESP PROT Z88.1-1969.

=====  
Physical/Chemical Properties  
=====

HCC:N1

Boiling Pt:B.P. Text:506F

Spec Gravity:0.884

Solubility in Water:NEGLIGIBLE

Appearance and Odor:VERY FLUID,MINERAL OIL ODOR,COLOR-ASTM L,0.5 TYP

=====  
Stability and Reactivity Data  
=====

==

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:OVERHEATING FOR EXTENDED PERIODS CAUSES DEGRADATION, NON HAZ

=====  
Disposal Considerations  
=====

Waste Disposal Methods:MUST BE DISPOSED OF IAW LOCAL, STATE, FED REG

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressl

y or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.