

ILLINOIS BRONZE PAINT CO -- LACQUER SPRAY PAINT -- 8010-00-965-2390

=====
Product Identification
=====

Product ID:LACQUER SPRAY PAINT

MSDS Date:01/01/1987

FSC:8010

NIIN:00-965-2390

MSDS Number: BFZRN

=== Responsible Party ===

Company Name:ILLINOIS BRONZE PAINT CO

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Info Phone Num:312-488-8001

Emergency Phone Num:800-228

-5635

CAGE:91794

=== Contractor Identification ===

Company Name:ILLINOIS BRONZE PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Phone:800-228-5635

CAGE:91794

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 10%

ACGIH TLV:500 PPM

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 13%

OSHA PEL:100 PPM

Ingr

ed Name:METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 29.0%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM; Z-2

ACGIH TLV:50 PPM, A2; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTANE-PROPANE (50-50 MOL WT%)

Fraction by Wt: 33.0%

=====
===== Hazards Identification =====

Effects of Overexposure:INHAL:ANEST:IRRIT OF RESPIRAT TRACT OR ACUT
NERV SYS DEPRESSION,HDACH,DIZZ,STAG GAIT,UNCONSCON,COM
A

=====
===== First Aid Measures =====

First Aid:FUMES:REMOV FR EXPOS.GET FRESH AIR.SPRAY(EYES)FLUSH
IMMED.W/LG QTY OF RUNNING WATER F/AT LEAST 15 MIN.TAKE TO A
DR.SPRAY(SKIN):WIPE OFF W/TOWEL.REMOV REMAIN W/MINERAL
SPIRITS,TURPENTINE OR LACQUER THI NNER,IN CASEOF LACQ.WASH W/SOAP &
WATR.REMOV CONTA

=====
===== Fire Fighting Measures =====

Flash Point:-40 F-40 C

Extinguishing Media:USE NFPA CL B EXTING(CO*2,DRY CHEM
OR FOAM)F/CLIA

FLAMBL LIQ

Fire Fighting Procedures:WEAR GOGG & SELF CONTNEDBREATHING APPARAT.WATR
SPRAY MAY(SUP

Unusual Fire/Explosion Hazard:CNS WILL RUPTR FRINTERNAL PRESSR AT ABOUT
190 F & DSCHRG FLAMBL CONTENTS.TOXIC FUMES IF HTD TO DECOM

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOV ALL SOURCES OF IGNIT (FLAMES,HOT
SURFACES & ELECTRICAL,STATIC OR FRICTIONAL SPARKS).AVOID BREATHING
VAPORS.VENTILATE AREA.REMOV W/INERT

LOSED
CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.