

EXXON COMPANY -- 5114 EP GREASE -- 9150-00-985-7247

===== Product Identification =====

Product ID:5114 EP GREASE

MSDS Date:01/01/1985

FSC:9150

NIIN:00-985-7247

MSDS Number: BGBVJ

=== Responsible Party ===

Company Name:EXXON COMPANY

Emergency Phone Num:713-656-3424

CAGE:72447

=== Contractor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:U

S

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, U.S.A.

Address:ROOM 2344

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949

CAGE:72447

===== Composition/Information on Ingredients =====

Ingred Name:LITHIUM SOAP

Ingred Name:SYNTHETIC ESTERS

===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN IRRITATION. INJECTION OF GREASE INTO SKIN: SOFT TISSUE DAMAGE.

=====

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES. SKIN: WASH WITH SOAP & WATER. INJECTION UNDER SKIN: CONTACT PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:415F/212C (COC)

Lower Limits:1

Upper Limits:7

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER FOG OR SPRAY.

Fire Fighting Procedures:SELF-CONT BREATH APP,WATER SPRAY TO COOL EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:D

O NOT MIX OR STORE WITH STRONG OXIDANTS.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE LUBRICANT. ADD ABSORBENT TO SPILL AREA. KEEP PETROLEUM PRODUCTS OUT OF SEWERS & WATER COURSES BY DIKING OR IMPOUNDING.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT,SPARKS,FLAME, OR STRONG OXIDANTS.

Other Preca

utions:AVOID BREATHING OIL MIST. LAUNDRER OIL SOAKED CLOTHING BEFORE REUSE. DISCARD LUBRICANT-SOAKED SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.

Ventilation:LOCAL

Protective Gloves:CHEM RESISTANT

Eye Protection:SPLASH GOGGLES/FACE SHIEL

Other Protective Equipment:CHEM RESISTANT APRON,COVERALLS.

Supplemental Safety and Health

CONTAINER SIZE: 6.5 LB CAN.

=====

==== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F/260C

Vapor Density:>10

Spec Gravity:0.94

Evaporation Rate & Reference: