View NSN Online: https://aerobasegroup.kr/nsn/3439-00-995-6750

Product ID: TECHALLOY AWS 309/316L/347 MSDS Date:09/01/1989 FSC:3439 NIIN:00-995-6750 **MSDS Number: BGCHL** === Responsible Party === Company Name: TECHALLOY MARYLAND INC, REID-AVERY DIV. Address:2310 CHESAPEAKE AVE. City:BALTIMORE State:MD ZIP:21222-4012 Country:US Info Phone Nu m:301-633-9300, 800-638-1458 Emergency Phone Num:301-633-9300, 800-638-1458 CAGE:59711 === Contractor Identification === Company Name: TECHALLOY COMPANY, INC. Address:2310 CHESAPEAKE AVENUE Box:City:BALTIMORE State:MD ZIP:21222 Country:US Phone:410-633-9300; 800-638-1458 CAGE:59711 

Ingred Name:IRON CAS:7439-89-6 RTECS #:NO4565500 Fraction by Wt: 45-80% Other REC Limits:5 MG/M3

Ingred Name:CHROMIUM (SARA III) CAS:7440-47-3 RTE CS #:GB4200000 Fraction by Wt: 11-32% Other REC Limits:NONE SPECIFIED BY M. OSHA PEL:1 MG/M3 ACGIH TLV:0.5 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA III) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 4-37% Other REC Limits:NONE SPECIFIED BY M. OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9192

Ingred Name:MANGANESE (SARA III) CAS:7439-96-5 RTECS #:OO9275000 Fraction by Wt: 0.5-2.5% Other REC Limits:NONE SPECIFIED BY M. OSHA PEL:(C) 5 MG/M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:SILICON CAS:7440-21-3 RTECS #:VW0400000 Fraction by Wt: 0.1-1.0% Other REC Limits:3 MG/M3 AS SIO2 OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MOLYBDENUM CAS:7439-98-7 RTECS #:QA4680000 Fraction by Wt: 0-4% Other REC Limits:NONE SPECIFIED BY M. OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:Y

ES OSHA:NO Health Hazards Acute and Chronic:SHORT TERM EXPOSURE TO WELDING FUMES, GASES OR DUST MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE NOTED. A CUTE EXPOSURE FROM SOME TOXIC GASES MAYCAUSE PULMONARY EDEMA, ASPHYXIATION AND EXCESSIVE EXPOSURE CAN BE FATAL. Explanation of Carcinogenicity:NICKEL & CHROMIUM ARE LISTED AS CARCINOGENIC. Effects of Overexposure:COUGHING, DIFFIC ULTY IN BREATHING, DIZZINESS, NAUSEA. Medical Cond Aggravated by Exposure: PULMONARY DISEASES. First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT: COOL BURNS WITH ICE WATER, WASH METAL POWDER WITH SOAP AND WATE R. GET MED ATTENTION BURNS. INGESTION: DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY. ====== Extinguishing Media: USE PROPER MEDIA FOR SURROUNDING FIRE. Fire Fighting Procedures: NEED TO WEAR PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:WELDING ARC & SPARKS CAN IGNITE COMBUSTIBLES. Spill Release Procedures: WEAR DUST MASK FOR DUSTY CONDITIONS. PICK UP OR SCOOP UP RODS FOR REUSE OR DISPOSAL. \_\_\_\_\_ Handling and Storage Precautions: STORE AT A DRY PLACE. Respiratory Protection: USE AIR SUPPLIED RESPIRATOR OR SCBA WHEN WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV. Ventilation: USE ADEQUATE GENERAL VENTILATION & LOCAL EXHAUST AT THE ARC. Protective Gloves:WELDER'S GLOVES Eye Protection: HELMET/FACE SHIELD WITH FILTER LENS. Other Protective Equipme

nt:WEAR PROTECTIVE CLOTHING. Work Hygienic Practices:WEAR PROTECTIVE GLSSES FOR ARC RAYS. WASH HANDS BEFORE EATING OF DRINKING. Supplemental Safety and Health FUMES, GASES, ARC RAYS AND ELECTRIC SHOCK CAN BE DANGEROUS TO YOUR HEALTH. FOR MORE INFO SEE ASZ 49.1-1983.

HCC:N1 Solubility in Water:INSOLUBLE Appearance and Odor:SOLID WIRE OR ROD. Percent Volatiles by Volume:0

================= Stability and Reactivity Dat

a ================

Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE STATED Hazardous Decomposition Products:OXIDES OF IRON,CHROMIUM,NICKLE,MANGANESE,SILICON AND MOLYBDENUM.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elemen ts of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.