

AMERON INC. -- AMERCOAT,78 RESIN RED -- 8010-00-997-2610

=====  
Product Identification  
=====

Product ID:AMERCOAT,78 RESIN RED

MSDS Date:01/01/1987

FSC:8010

NIIN:00-997-2610

Kit Part:Y

MSDS Number: BGCKR

=== Responsible Party ===

Company Name:AMERON INC.

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:JO831

=== Contractor Identification ===

Company Name:AMERON INC.

Address:

201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:JO831

Company Name:AMERON INTERNATIONAL PROTECTIVE COATINGS GROUP

Address:201 NORTH BERRY ST.

Box:City:BREA

State:CA

ZIP:92821

Country:US

Phone:714-529-1951

CAGE:55849

=====  
Composition/Information on Ingredients  
=====

Ingred Name:COAL TAR, CAS# 8007-45-2

CAS:8007-45-2

RTECS #:GF8600000

Fraction by Wt: 23%

ACGIH TLV:0.2 MG/CUM

Ingred Name:EPOXY RESIN, CAS# 65068-38-6

Fraction by Wt: 18%

ACGIH TLV:2 PPM(SKIN

)  
Ingred Name:NAPHTHALENE (SARA III)  
CAS:91-20-3  
RTECS #:QJ0525000  
Fraction by Wt: 12%  
OSHA PEL:10 PPM/15 STEL  
ACGIH TLV:10 PPM/15 STEL; 9192  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:METHYL N-AMYL KETONE  
CAS:110-43-0  
RTECS #:MJ5075000  
Fraction by Wt: 4%  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fraction by Wt: 2%  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150 STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:  
1000 LBS

=====  
===== Hazards Identification =====

Effects of Overexposure:IRRIT:SKIN,MUC MEMB,EYE,RESP  
SYS.INHAL:HDCH,NAUS,DIZ,ASPHYXIA.SKIN SENSITIZATION.OTH PRECAUTION.

=====  
===== First Aid Measures =====

First Aid:INHAL:FRESH AIR.GIVE O\*2,CPR.SKIN:WASH THOROUGHLY WITH SOAP  
AND WATER.EYE:FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MIN AND  
GET MEDICAL ATTENTION.LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.INGEST: D  
O NOT INDUCE VOMITING;CALL PHYSICIAN IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point:107F,42C SCC  
Lower Limits:1.1  
Extinguishing Media:FOAM,CO\*2,DRY CHEMICAL  
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT,ELECRICAL  
EQUIPMENT,SPARKS AND OPEN FLAME.WEAR SELF-CONTAINED BREATHING  
APPARATUS

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION.USE  
ABSORBENT CLEANUP M

ATERIALS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.STORE IN COOL, DRY, WELL-VENTILATED AREA.AVOID PROLONGED BREATHING OF VAPORS, SPRAY MIST, CONTACT W/ SKIN, EYES.

Other Precautions:WEAR PROTECTIVE BARRIER CREAM ON EXPOSED SKIN.OVEREXPOS:INHAL, INGEST, ABSORB THRU THE SKIN CAN BE HARMFUL.KIDNEY, LIVER DAMAGE MAY OCCUR.SKIN IRRITATION ACCENTUATED BY SUNLIGHT.

=====  
===== Exposure Co  
ntrols/Personal Protection =====

Ventilation:SUFFICIENT VENTILATION TO KEEP AIR CONTAMINANT CONC 1

Spec Gravity:1.51

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:RED LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:31

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT, OPEN FLAME, ARC OR

SPARKS, LIGHT:PHOTOCHEMICALLY R

EACTIVE

Hazardous Decomposition Products:CO, CO\*2, NO\*X.BURN, WELD PRODUCE COAL

TAR FUME KEEP