Product ID:ACETONE MSDS Date:01/05/1994 FSC:6810 NIIN:01-003-0262 MSDS Number: BGCPG === Responsible Party === Company Name: J.T. BAKER CHEMICAL CO Address:222 RED SCHOOL LANE City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Info Phone Num:800-JTBAKER Emergency Phone Num:(201) 859-2151/800-424-9300(CHEMTR) CAGE:D 0870 === Contractor Identification === Company Name: J.T. BAKER CHEMICAL CO. Address:222 RED SCHOOL LANE City:PHILLIPSBURG State:NJ ZIP:08865-2219 Country:US Phone:201-859-2151 CAGE:DO870 Company Name: MALLINCKRODT BAKER, INC. Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:800-582-2537 CAGE:70829

Ingred Name:ACETONE (SARA III) CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 90-100% OSHA PEL: 1000PPM ACGIH TLV:750PPM/1000STEL;9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 9750 MG/KG. Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALED:IRRITATION NOSE, THROAT, HEADACHE, NAUSEA, VOMITING, DIZZINESS, NARCOSIS, RESPIRATORY FAILURE, LOW BLOOD PRESSURE, CNS DEPRESSION, COMA. SKIN:I **RRITATION, POSSIBLE DERMATITIS** &/OR ABSORPTION. EYE:SEVERE IRRITATION, POSSIBLE TEMP CORNEAL DAMAGE. INGESTED: G/I IRRITATION, HEADACHE, NAUSEA, CNS DEPRES. CHRONIC:LIVER/KIDNEY DAMAG **Explanation of Carcinogenicity:NONE IDENTIFIED** Effects of Overexposure: INHALED: IRRITATION NOSE, THROAT, HEADACHE, NAUSEA, VOMITING, DIZZINESS, NARCOSIS, RESPIRATORY FAILURE, LOW BLOOD PRESSURE, CNS DEPRESSION, COMA. SKIN: IRRITATION POSSIBLE DERMATITIS. EYE:SEVERE IRRITATION, POSS IBLE TEMP CORNEAL DAMAGE. **INGESTED:G/I** IRRITATION, HEADACHE, NAUSEA, DIZZINESS, CNS DEPRESSION. Medical Cond Aggravated by Exposure: CHRONIC RESPIRATORY DISEASE, SKIN DISORDERS, EYE DISORDERS. First Aid: IF ANY IRRITATION PERSISTS OR IS SEVERE, SEE A DOCTOR.

EYE:FLUSH W/WATER 15 MIN. SKIN:FLUSH WITH WATER. INHALED:REMOVE TO FRESH AIR. AID/RESTORE BREATHING IF NECESSARY. INGESTED:DO NOT INDUCE VOMITING . GIVE LARGE AMOUNTS WATER. NOTHIN

G BY MOUTH IF

UNCONSCIOUS. NOTE TO PHYSICIAN:ASPIRATION HAZARD! IF NECESSARY TO EVACUATE STOMACH, USE METHOD LEAST LIKELY TO CAUSE ASPIRATION INTO LUNGS.

Flash Point Method:CC Flash Point:-2F,-18C Lower Limits:2.2% Upper Limits:13% Extinguishing Media:USE ALCOHOL FOAM, DRY CHEMICAL OR CO2. (WATER MAY BE INEFFECTIVE). Fire Fighting Procedures:WEAR PROPER PROTECTIVE EQUIPMENT AND SCBA W/ FULL FACEPIECE OPERA

TED PRESSURE DEMAND MODE. USE WATER TO KEEP FIRE- EXPOSED CONTAINERS COOL. Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND OR FLOOR, THEN 'FLASH BACK' FROM A DISTANT IGNITION SOURCE. CONTACT W/STRONG OXIDIZERS MAY CAUSE FIRE. Spill Release Procedures: WEAR SUITABLE PROTECTIVE CLOTHING. ELIMINATE ALL IGNITION SOURCES. STOP LEAK IF POSSIBLE W/OUT RISK. USE H2O SPRAY TO RED UCE VAPORS. TAKE UP W/SAND/OTHER NON-COMBUSTIBLE ABSORBANT & PLACE INTO CONTAIN ER FOR DISPOSAL. FLUSH AREA W/WATER. Neutralizing Agent:NOT APPLICABLE. Handling and Storage Precautions: KEEP TIGHTLY CLOSED. STORE IN COOL, DRY, WELL- VENTED, FLAMMABLE LIQUID STORAGE AREA. ISOLATE FROM INCOMPATIBLE MATERIALS. Other Precautions: BOND & GROUND CONTAINERS WHEN TRANSFERRING LIQUID. ======== Exposure Controls/Personal P rotection ========= Respiratory Protection: RESPIRATORY PROTECTION REQUIRED ABOVE TLV: AT CONCENTRATIONS UP TO 5000 PPM, CHEMICAL CARTRIDGE RESPIRATOR W/ORGANIC VAPOR CARTRIDGE IS RECOMMENDED. ABOVE THIS LEVEL, AN SCBA IS RECOMMENDED. Ventilation: USE GENERAL OR LOCAL EXHAUST VENTILATION TO MEET TLV REQUIREMENTS. Protective Gloves: BUTYL RUBBER GLOVES. Eye Protection: SAFETY (CHEMICAL SPLASH) GOGGLES Other Protective Equipment: NO FURTHER EQUIPMENT GIVEN ON MSDS BY MFR. Work Hyg ienic Practices:MFR: ? HMIS:USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING. Supplemental Safety and Health NONE HCC:F2 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:133F.56C Melt/Freeze Pt:M.P/F.P Text:-139F,-95C Vapor Pres:184 MM Vapor Density:2.0 Spec Gravity:0.79 Evaporation Rate & amp; Reference:14.4 (BUTYL ACETATE=1) Solubility in Water:COMPLETE (100%)

Appear

ance and Odor:CLEAR, COLORLESS LIQUID. SWEET ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS, STRONG ACIDS & BASES, HALOGEN COMPOUNDS, AMINES & AMMONIA,
Stability Condition to Avoid:HEAT, FLAME, OTHER SOURCES OF IGNITION.
Hazardous Decomposition Products:CO, CO2.
Conditions to Avoid Polymerization:WILL NOT OCCUR

=====

Waste Disposal Methods:DISPOSE I/A/W ALL APPLICABLE FEDERAL, STATE & LOCAL ENVIRONMENTAL REGULATIONS. EPA HAZARDOUS WASTE NUMBER:U002 HMIS SUGGESTS INCINERATION AS DISPOSAL METHOD.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability

for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.