

ARCOS CORP. -- STAINLEND 316L -- 3439-01-027-4800

=====
Product Identification
=====

Product ID:STAINLEND 316L

MSDS Date:01/01/1985

FSC:3439

NIIN:01-027-4800

MSDS Number: BGFRM

=== Responsible Party ===

Company Name:ARCOS CORP.

Emergency Phone Num:717-339-5200

CAGE:MO615

=== Contractor Identification ===

Company Name:ARCOS ALLOYS DIV OF HOSKINS MFG CO

Address:#1 ARCOS DRIVE

Box:308

City:MTCARMEL

S

tate:PA

ZIP:17851

Country:US

Phone:717-339-5200, CHEMTREC 800-424-9300

CAGE:03805

Company Name:ARCOS CORP.

CAGE:MO615

=====
Composition/Information on Ingredients
=====

Ingred Name:CHROMIUM (SARA III)

CAS:7440-47-3

RTECS #:GB4200000

Fraction by Wt: 14.0%

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 9.0%

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred Name:ARSENIC

FLUORIDE (FOR OSHA PEL SEE 29CFR 1910.1018)

CAS:7784-35-2

RTECS #:CG5775000

Fraction by Wt: 1.0%

OSHA PEL:0.01 MG/M3 (AS)

ACGIH TLV:0.2 MG/M3 (AS); 8990

Ingred Name:MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:OO9275000

Fraction by Wt: 1.5%

OSHA PEL:(C) 5 MG/M3 DUST

ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:IRON ION (FE +2)

CAS:15438-31-0

RTECS #:NO6925000

Fraction by Wt: 44.0%

OSHA PEL:1 MG/M3 (FE)

ACGIH TLV:1 MG/M3 (FE); 8990

=====
===== Hazards Identification =====

Effects of Overexposure:CAN CAUSE PULMONARY IRRITATION FROM DUST
INHALATION IF USE W/O WEARING PROPER PROTECTIVE EQUIPMENTS.

=====
===== First Aid Measures =====

First Aid:REMOVE TO FRESH AIR.CALL DR. IF BREATHING IN FRESH AIR IS
DIFFICULT OR IRRITATION PERSISTS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR INORGANIC ACIDS.WEAR
SAFETY SHOES DURING HANDLING/STORING.

Other Pre

cautions:ARC & SPARK COULD BE SOURCE OF IGN.DO NOT USE NEAR
IGNITABLE MATERIAL BECAUSE IGNITABLE MATERIAL MAY IGNITE EXPLOSIVELY.MATERIAL
IS NON-HAZ,IT MAY BE HAZ. TO USING PERSON WHEN USED W/O PROPER
PROTECTIVE EQUIP

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELD FUME RESP. OR AIRLINE RESP. FOR CONFINED
SPACE.

Ventilation:LOCAL & MECH(GEN):SEMI-OPEN OR PROPERLY VENTILATED AREA.

Protective Gloves:WELDERS PROTECT

Eye Protection:SEE SUPP DATA**

O

ther Protective Equipment:WELDERS CLOTHING FOR PROTECTION AGAINST SPARKS/HOT MATERIAL.

Supplemental Safety and Health

HAZ.INGRED:TITANIUM DIOXIDE,11%,15MG/CUM;LIMESTONE,5%,15 MG/CUM;POTASSIUM SILICATE,6%,15 MG/CUM;FERROALLOYS,5%,10MG/CUM;MOLYBDENUM,METALLIC,1.5%,15 MG/CUM.**FACE SHIELD & SAFETY GLAGG #12 SHAD

===== Physical/Chemical Properties =====

HCC:N1

===== Stability and Reactivity Data =====

Stability Indicator/Mater

ials to Avoid:YES

Hazardous Decomposition Products:CO,CO*2,OZONE,OXIDES OF NITROGEN

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assum e responsibility for the suitability of this information to their particular situation.