

GOLDEN BEAR DIV OF WITCO MFG CO -- MIL-L-2105C,LUBRICATING OIL,GEAR,GRD 80W-90 --
9150-01-035-5392

=====
Product Identification
=====

Product ID:MIL-L-2105C,LUBRICATING OIL,GEAR,GRD 80W-90

MSDS Date:01/01/1987

FSC:9150

NIIN:01-035-5392

MSDS Number: BGGJR

=== Responsible Party ===

Company Name:GOLDEN BEAR DIV OF WITCO MFG CO

Emergency Phone Num:805-393-7110

CAGE:KO503

=== Contractor Identification

===

Company Name:GOLDEN BEAR DIV WITCO MFG CO

Box:5446

CAGE:KO503

Company Name:WITCO CORP GOLDEN BEAR DIVISION

Address:10100 SANTA MONICA BLVD SUITE 1470

City:LOS ANGELES

State:CA

ZIP:90067

Country:US

Phone:805-393-7110

CAGE:07750

=====
Composition/Information on Ingredients
=====

Ingred Name:LUBRICATING OIL (A HOMOGENEOUS PETROLEUM PRODUCTS).

Ingred Name:ADDITIVES(TYPE NOT SPECIFIED)

=====
Hazards Identification
=====

Effects of Overexpo

sure:SKIN:IRRIT/DERMATITIS ON PROLNKD

CONTCT;EYES:MAY CAUSE IRRIT;INH/INGEST:NOT STATED BY MFR.

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES:FLUSH W
LG AMTS H*2O FOR 15 MIN;SKIN:FLUSH W LG AMTS H*2O;INGEST:RINSE
MOUTH.GET MED ATTN.

=====
Fire Fighting Measures
=====

Flash Point:>149C/>300F(COC)

Extinguishing Media:CO*2,DRY CHEM,WATER SPRAY OR FOAM;WATER INEFF.

WATER

FROTHES.

Fire Fighting Procedures:NO WATER ON MATL. WATER SPRAY TO ABSORB VAPOR/COOL CONT.

Unusual Fire/Explosion Hazard:AVOID USE OF WATER ON FIRES;CAUSES DENSE SMOKE.CONTNRS MAY EXPLODE IN HEAT OF FIRE.COOL W/H*2O

===== Accidental Release Measures =====

Spill Release Procedures:IN CASE OF SPILL OR LEAK ABSORB W/AN INERT ABSORBENT SUCH AS SAND,CLAY OR VERMICULITE & SWEEP UP.PLACE IN CLOSED CONTAINER DURING CLEAN UP,USE PROTCTV EQUIP TO PROTECT BODY CONTACT & CLOTHING;IF SPILL ED IN H*2O,RMV BULK OF PRODUCT BY SKIMMING.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W/SKIN OR BREATHING OF VAP,MISTS OR FUMES.LAUNDER CONTAMNTD CLOTHG BEFORE USE.KEEP CONTNRS TIGHTLY CLOSED.AVOID STRONG OXIDZRS.ELIM SOURCE OF IGNITION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/OSHA APPRVD RESP W/ORGANIC VAP CARTRIDGE IF VAP >PEL.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

MSDS FROM MFR DATED:4/11/86; SP GRAVITY RANGE:0.8

9 TO

0.99;VISCOSITY=>18.6 CST @ 40C; WHERE MIST IS GENERATED,OBSERVE A PEL OF MG/CUM FOR MINERAL OIL MIST.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>288C/>550F

Vapor Pres: