

DELTA PETROLEUM CO,INC -- GEAR OIL 85W/140 -- 9150-01-035-5395

===== Product Identification =====

Product ID:GEAR OIL 85W/140

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5395

MSDS Number: BGGNW

=== Responsible Party ===

Company Name:DELTA PETROLEUM CO,INC

Emergency Phone Num:(504) 833-2861

CAGE:7A348

=== Contractor Identification ===

Company Name:DELTA PETROLEUM CO., INC

Address:10352 RIVER ROAD,

B

ox:10397

City:ST. ROSE

State:LA

ZIP:70087

Country:US

Phone:504-832-2732

CAGE:7A348

===== Composition/Information on Ingredients =====

Ingred Name:OILS,LUBRICATING

Ingred Name:PHOSPHORUS COMPOUNDS

Ingred Name:SULFUR

===== Hazards Identification =====

Effects of Overexposure:LOW ODER OF TOXICITY & IRRITANCY

===== First Aid Measures =====

First Aid:IF LIQUID CONTACTS EYES,FLUSH PROMPTY WITH WATER UNTIL

ANY

IRRITATION SUBSIDES.SKIN-WASH WITH SOAP & WATER

=====  
Fire Fighting Measures  
=====

Flash Point:180C,356F COC

Extinguishing Media:FOAM,DRY CHEMICAL,WATER SPRAY,WATER FOG,CARBON DIOXIDE

Fire Fighting Procedures:USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES

Unusual Fire/Explosion Hazard:RESPIRATORY PROTECTION REQUIRED FOR FIRE FIGHTING PERSONNEL

=====  
Accidental Release Measures  
=====

Spill Release Procedures:KEEP PU

BLIC AWAY.SHUT OFF SOURCE IF

POSSIBLE.DIKE WITH SAND OR EARTH.NOTIFY APPROPRIATE AUTHORITIES IF SUBSTANCE HAS ENTERED WATER COURSE OR SEWER

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE.KEEP AWAY FROM HEAT & OPEN FLAME.DO NOT STORE NEAR FLAME OR STRONG OXIDING AGENTS

Other Precautions:AVOID EYE CONTACT &PROLONGED OR REPEATED SKIN CONTACT.AVOID BREATHING OIL MIST.WASH OFF AFTER HANDLING

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USUALLY NOT NEEDED

Ventilation:LOCAL USUALLY NOT NEEDED IF USED IN OPEN AREA

Protective Gloves:NEOPRENE/PLAST.

Eye Protection:SAFETY GLASS/FACE SHIELD

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:V6

Boiling Pt:B.P. Text:>600F,IBP

Vapor Pres:5

Vapor Density:>1

Spec Gravity:0.905

Evaporation Rate & Reference:NEGLIGIBLE

Solubility in Wate

r:NEGLIGIBLE

Appearance and Odor:LIQUID,MODERATE ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:DO NOT HEAT ABOVE 140F FOR LONG PERIODS

Hazardous Decomposition Products:HYDROGEN SULFIDE MAY BE RELEASED IF  
HEATED ABOVE 140F

===== Disposal Considerations =====

Waste Disposal Methods:CONTAIN WITH A SUITABLE AB

SORBENT.PLACE IN

CONTAINERS SUITABLE FOR SHIPMENT TO DISPOSAL AREA.LONG RANGE  
DISPOSAL CAN BE INCINERATION OR LANDFILL IF PROCEDURE CONFORMS TO  
LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any pers

on utilizing this

document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.