View NSN Online: https://aerobasegroup.kr/nsn/6750-01-040-1114

EASTMAN KODAK COMPANY -- 140 4151,KODALITH RT LIQ DEVELOPR,PSART A 6750-01-040-1114

Product ID:140 4151, KODALITH RT LIQ DEVELOPR, PSART A

MSDS Date:07/25/1984

FSC:6750

NIIN:01-040-1114

Kit Part:Y

MSDS Number: BGGZZ === Responsible Party ===

Company Name: EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY ZIP:14650 Country:US

Info Phone Num:71

6-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:WATER; (45-50%)

CAS:7732-18-5

RTECS #:ZC0110000 Fraction by Wt: 47.5%

Ingred Name:SODIUM FORMALDEHYDE BISULFITE (20-25%)

CAS:870-72-4 RTECS #:PB2200 000

Fraction by Wt: 22.5%

Ingred Name:TRIETHYLENE GLYCOL (15-20%)

CAS:112-27-6

RTECS #:YE4550000 Fraction by Wt: 17.5%

Ingred Name: HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000 Fraction by Wt: 07.5% OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

=========== Hazards Identification ==========================

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:AC

UTE:MAY CAUSE SKIN/EYES IRRITATION

ON CONTACT; CHRONIC: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION AND MAY CAUSE SKIN ALLERGIC REACTION.

Effects of Overexposure:EYES,SKIN:IRRITNT;REPEATED SKIN CONTACT MAY CAUSE ALLERGIC SKIN REACTION;INGEST:HARMFUL

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*2 IF NEED;EYES:FLUSH W LG AMTS H*20 FOR 15 MIN;SKIN:FLUSH W LG AMTS H*20;INGEST:RINSE MOUTH;GET IMMED

IATE MEDICAL ATTENTION FOR EYES OR INGEST.

========= Fire Fighting Measures ===============


Flash Point:NONE

Extinguishing Media: SUITABLE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN & EYES.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF DECOMPOSITION PRODUCTS.

======== Accidental Release Measures ============

Spill Release P



s to Avoid:YES
MINERAL ACIDS,STRONG OXIDIZERS
Stability Condition to Avoid:HEAT,HIGH TEMPERATURES.
Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL EMIT OXIDES
OF CARBON, S, & N*2.

======= Disposal Considerations ===========

Waste Disposal Methods: MANUFACTURER STATES THAT DISCHARGE, TREATMENT, OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE, OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formu lated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.