

BENSON,INC. -- 980895-02,BENSON MODEL C CONCENTRATE -- 6850-01-042-0697

=====
Product Identification
=====

Product ID:980895-02,BENSON MODEL C CONCENTRATE

MSDS Date:01/01/1987

FSC:6850

NIIN:01-042-0697

MSDS Number: BGHDW

=== Responsible Party ===

Company Name:BENSON,INC.

Emergency Phone Num:415-964-7900,X-561

CAGE:MO703

=== Contractor Identification ===

Company Name:BENSON INC.

CAGE:4X257

Company

Name:BENSON,INC.

CAGE:MO703

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPARAFFINIC HYDROCARBONS (CAS#64742-48-9)

Fraction by Wt: 85%

ACGIH TLV:300PPM

Ingred Name:POLYMERS

Fraction by Wt: 10%

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 5%

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

=====
Hazards Identification
=====

Effects of Overexposure:HIGH VAPOR CONC ARE IRRITATING TO
EYES,RESPIR

ATORY TRACT;CAUSE HEADACHE & MAY AFFECT CENTR NERVE SYS

=====
First Aid Measures
=====

First Aid:INHALATION:REMOVE FROM SOLVENT-LADEN AREA TO FRESH-AIR AREA.ACCIDENTAL INGESTION:DO NOT INDUCE VOMITING;CALL DOCTOR IMMEDIATELY.EYES-FLUSH THOROUGHLY WITH CLEAN WARM WATER FOR AT LEAST 15 MINS.IF IRRITATION PERSISTS,CALL DOCTOR.

=====
Fire Fighting Measures
=====

Flash Point:104F/40C(TCC)
Autoignition Temp:Autoignition Temp Text:559F
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:AVOID WATER-IT TENDS TO SPREAD HYDROCARBON SOLV FIRES;W.SCBA
Unusual Fire/Explosion Hazard:FLAMM.VAPOR MAY SPREAD AWAY FROM SPILL.CONT.MAY EXPLODE IN HT.OF FIRE.VAP.EXPL.HAZ.INDOORS,OUTDOORS.

=====
Accidental Release Measures
=====

Spill Release Procedures:SHUT OFF & ELIMINATE IGNITION SOURCES.KEEP PEOPLE AWAY.RECOVER FREE PRODUCT.ADD SNAD,EARTH OR OTHER ABSORBENT TO SPILL AREA.VENTILATE CONFINED SPACE.KEEP OUT OF SEWERS AND WATERCOURSES BY DIKING OR IMPOUNDING.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.AVOID STORAGE NEAR HEAT,STRONG LIGHT(IF CONTAINERS ARE CLEAR),SPARKS,OR OPEN FLAME.STORE IN COOL,DRY WELL VENTILATED AREA.
Other Precautions:AVOID USE IN A SMALL CLOSED ROOM OR IN A CONFINED AREA WITH POOR AIR CIRCULATION.PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NORMAL AIR CONDITIONING IS ADEQUATE,RESP.PROTECTION(SPEC) NOT NEEDED
Ventilation:NOT NEEDED PER MFR.
Protective Gloves:N/A PER MFR.
Eye Protection:N/A,PER MFR
Supplemental Safety and Health
MSDS DATED 4-30-86.

=====
Physical/Chemical Properties
=====

HCC:F4
Boiling Pt:B.P. Text:320-375F
Vapor Pres:36
Vapor Density:

5.05

Spec Gravity:0.81

Evaporation Rate & Reference:0.25,BUTYL ACETATE

Solubility in Water: