View NSN Online: https://aerobasegroup.com/nsn/6850-01-045-7931

## ELDORADO CHEMICAL COMPANY, INC -- ED-394; AIRCRAFT CLEANER -- 6850-01-045-7931

Product ID:ED-394;AIRCRAFT CLEANER

MSDS Date:01/17/1992

FSC:6850

NIIN:01-045-7931

MSDS Number: BGHMX === Responsible Party ===

Company Name: ELDORADO CHEMICAL COMPANY, INC

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX ZIP:78265 Country:US

Info Phone Num:512-653-9323/0825 Emergency Phone Num:(800)531-1088

Preparer's Name: PAT E. SMITH

CAGE:55208

=== Contractor Identification ===

Company Name: ELDORADO CHEMICAL COMPANY, INC.

Address:14350 LOOKOUT ROAD

Box:34837

City:SAN ANTONIO

State:TX

ZIP:78265-4837 Country:US

Phone:800-531-1088/210-653-2060

CAGE:55208

======= Composition/Information on Ingredients ========

Ingred Name: ALIPHATIC PETROLEUM NAPHTHAS

CAS:68476-34-6 Fraction by Wt: 12.0%

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fract

Ingred Name:UNIDENTIFIED COMPONENTS ACGIH TLV:NOT SPECIFIED
======================================
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Health Hazards Acute and Chronic:ACUTE IRRITATION OF EYES AND SKIN AND RESPIRATORY TRACT;BURNING OF EYES;CNS EFFECTS,IRRITATION,DIZZINESS,NAUSEA,FATIGUE. CHRONIC:DERMATITIS. Explanation of Carcinogenicity:NO DATA AVAILABLE (PER MSDS) Effects of
Overexposure:INHAL:DIZZINESS,NAUSEA,HEADACHES;SKIN:IRRITANT,DEFAT BURNS,DERMATITIS;EYES;CORROSIVE,MODERATE PAIN. Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.
======================================
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.
====== ======== Fire Fighting Measures ======================
Flash Point:NONE Extinguishing Media:ANY SUITABLE MEDIA FOR SURROUNDING FIRES Fire Fighting Procedures:NONE NOTED:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA. Unusual Fire/Explosion Hazard:NONE NOTED
========== Accidental Release Measures ===========
Spill Release Procedures:USE PROPER PERSONAL PROTECTION;DILUTE WITH WATER AND RECOVER FOR PROPER DISPOSAL.SEPERATE PETROLEUM FRACTION
=======================================

ion by Wt: 5.0% OSHA PEL:S, 50 PPM ACGIH TLV:S, 25 PPM; 9293 === Handling and Storage =========

Handling and Storage Precautions:STORE IN COOL DRY AND WELL VENTILATED AREA.KEEP AWAY FROM HEAT,OPEN FLAMES;KEEP CONTAINE CLOSED WHEN NOT IN USE

Other Precautions: AVOID CONTACT WITH EYES AND SKIN.DO NOT INHALE VAPORS/MIST.WASH THOROUGHLY AFTER EACH USE.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORG. VAPORS/MIST IF ABOVE TLV Ventilation:PROVID E MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN