

TEXSTAR AUTOMOTIVE GROUP -- GEAR LUBRICANT(GRADE 75W) -- 9150-01-048-4593

=====  
Product Identification  
=====

Product ID:GEAR LUBRICANT(GRADE 75W)

MSDS Date:01/01/1985

FSC:9150

NIIN:01-048-4593

MSDS Number: BGHVH

=== Responsible Party ===

Company Name:TEXSTAR AUTOMOTIVE GROUP

Emergency Phone Num:314-521-3900

CAGE:1ER44

=== Contractor Identification ===

Company Name:TEXSTAR AUTOMOTIVE GROUP INC

Add

ress:9060 LATTY AVE

Box:City:ST LOUIS

State:MO

ZIP:63134-1027

Country:US

Phone:314-521-3900

CAGE:1ER44

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LUBRICATING OIL

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITANT FROM PROLONGED/REPEATED EXPOSURE TO SKIN.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP AND WA  
RM WATER, THOROUGHLY.

=====  
Fire Fighting Measures  
=====

Flash Point:430F, 221.1C,COC

Lower Limits:1

Upper Limits:6

Extinguishing Media:FOAM, DRY CHEMICAL, CO\*2, WATER FOG OR SPRAY

Fire Fighting Procedures:RESPIRATORY PROTECTION REQUIRED.

Unusual Fire/Explosion Hazard:FUMES, SMOKE, OXIDES OF SULFUR, NITROGEN & CO\*2.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:RECOVER FREE LIQUID. ADD ABSORBENT SUCH AS

SAND, EARTH, OR SAWDUST TO SPILL AREA. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATERCOURSES BY DIKING OR IMPOUNDING. ADVISE AUTHORITIES IF PRODUCT HAS ENTE RED SEWERS, WATERCOURSES OR EXTENSIVE LAND AREA.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS

Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL SOAKED CLOTHING & LAUNDRER BEFORE REUSE. DISCARD OIL SOAKED SHOES. WASH SKIN WITH SOAP AND WATER AFTER USE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA AIR-SUP RESP IF WORKING IN CONFINED OR CLOSED AREA. (MFR)

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS-SEE SUPP DATA

Protective Gloves:CHEM RESISTANT

Eye Protection:CHEM SPLASH GOG/FACE SHLD

Other Protective Equipment:USE CHEM RESISTANT APRON OR OTHER CLOTHING TO AVOI

D CONTACT.

Supplemental Safety and Health

CONTAINER: 1 GAL CAN. MFR ADDRESS: 9060 LATTY AVENUE, ST. LOUIS MO.

63134. VP: 60 FPM HOOD OR FACE

VELOCITY FOR CONFINED SPACES.

=====  
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:675F, 357C

Vapor Density:> 12

Spec Gravity:0.88

Solubility in Water:NEGLIGIBLE

Appearance and Odor:LIQUID, MILD HYDROCARBON ODOR.

Percent Volatiles by Volume:0

=====  
===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

LIQUID CHLORINE, CONC O<sub>2</sub>, NA/CALYPOCHLORITE- STRONG OXIDANTS

Stability Condition to Avoid: STRONG OXIDANTS

Hazardous Decomposition Products: FUMES, SMOKE, CO & SULFUR OXIDES IN INCOMPLETE COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: MFR RECOMMENDS DISPOSING ABSORBENT MATERIAL IN AN APPROVED WASTE DISPOSAL SITE OR FACILITY. WASTE DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.