

PRATT & LAMBERT,INC.,INDUSTRIAL COATINGS DIV. -- 724112-68 POLYAMIDE RESIN;  
COMPONENT B -- 8010-01-048-6539

===== Product Identification =====

Product ID:724112-68 POLYAMIDE RESIN; COMPONENT B

MSDS Date:07/20/1988

FSC:8010

NIIN:01-048-6539

Kit Part:Y

MSDS Number: BGHXF

=== Responsible Party ===

Company Name:PRATT & LAMBERT,INC.,INDUSTRIAL COATINGS DIV.

Address:16116 E 13TH ST

Box:2153

City:WICHIT

A

State:KS

ZIP:67201

Country:US

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE

(SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)  
CAS:78-83-1  
RTECS #:NP9625000  
OSHA PEL:100 PPM  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:POLYAM  
IDE RESIN

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:PRODUCT IS AN IRRITANT AND THE  
SOLVENTS CAN WITH CHRONIC EXPOSURE CAUSE BRAIN,CENTRAL NERVOUS  
SYSTEM,AND/OR KIDNEY DAMAGE. DELIBERATELY CONCENTRATING AND  
BREATHING VAPORS MAY BE HARMFUL OR FATAL.  
Effects of Overexposure:EYE:IRRITATION. SKIN:IRRITATION,DEFATTING.

INHALED:RESPIRATORY IRRITATION,CENTRAL NERVOUS SYSTEM  
DEPRESSION,HEADACHE,DIZZINESS,NAUSEA,CONFUSION. INGESTED:G/I  
IRRITATION,NAUSEA,VOMITING. ASPIRATION INT O LUNGS MAY CAUSE  
CHEMICAL PNEUMONIA.  
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER. SKIN:REMOVE CONTAMINATED CLOTHING. WASH  
WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR.GIVE OXYGEN OR  
ARTIFICIAL RESPIRATION AS NEEDED. GE

T MEDICAL ATTENTION.

INGESTED:DO NOT IND UCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:24F/-4C

Extinguishing Media:NFPA CLASS B (CARBON DIOXIDE,DRY CHEMICAL,ALCOHOL FOAM, WATER MAY BE INEFFECTIVE).

Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS.WATER MAY BE USED TO COOL CONTAINERS. IF WATER USED,FOG NOZZLES PREFERRED.

Unusual Fire/Explosion Hazard:PRODUCT MAY EMIT TOXIC FUMES. SYM PTOMS MAY BE DELAYED.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. ABSORB ON INERT MATERIAL. PLACE IN TIGHTLY CLOSED CONTAINERS FOR DISPOSAL.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A WELL VENTILATED AREA BELOW 120F. DO NOT USE UNTIL SAFETY PRECAUTIONS AND DIRECTIONS HAVE BEEN READ AND UNDERSTOOD.

Other Precautions:DO NOT REUSE CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH RESPIRATOR FOR ORGANIC VAPORS OR SUPPLIED AIR RESPIRATOR IF IN ENCLOSED AREA OR EXPOSED ABOVE TLV.

Ventilation:PROVIDE GENERAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:SOLVENT IMPERMEABLE.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:SAFETY SHOWER EYEWASH.

Work Hygienic Practices:USE NORMAL CHEMICAL HYGIE NE.

Supplemental Safety and Health

FOR QUANTITY OF INGREDIENTS SEE THE APPROPRIATE REVISION OF THE SPEC.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:175-245F

Vapor Density:>AIR

Spec Gravity:0.83

Evaporation Rate & Reference: