

A.B. DICK COMPANY -- 4-3792 -- 6850-01-056-0947

===== Product Identification =====

Product ID:4-3792

MSDS Date:01/01/1987

FSC:6850

NIIN:01-056-0947

MSDS Number: BGJLM

=== Responsible Party ===

Company Name:A.B. DICK COMPANY

Address:5700 WEST TOUHY AVENUE

City:CHICAGO

State:IL

ZIP:60648-4606

Country:US

Info Phone Num:312-547-8800

Emergency Phone Num:312-647-8800

CAGE:17638

=== Contractor Identifica

tion ===

Company Name:DICK A B CO

Address:7400 CALDWELL AVE

Box:City:NILES

State:IL

ZIP:60714-4628

Country:US

Phone:847-779-1900

CAGE:17638

===== Composition/Information on Ingredients =====

Ingred Name:MIXED ISODECANES CAS# 68551-16-6

Fraction by Wt: 99%

ACGIH TLV:300 PPM

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 1%

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

===== Hazards Identification =====

Effects of

Overexposure:INHAL:HEADACHE,IRRIT:SKIN/EYES:IRRIT;INGEST:NAUSEA,HEADACHE & STOMACH UPSET.

=====
First Aid Measures
=====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHG GIVE CPR,IF BRTHG DIFF,GIVE OXYGEN. CONTACT;IMMED FLUSH EYES W/PLENTY OF WATER,WASH SKIN W/SOAP & WATER.RMV CONTAM CLTHG & SHOES.INGEST:DO NOT INDUCE VOMITING. GET MED ATTN IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash P
oint:102F/39C TCC
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:USE SCBA IN ENCLOSED AREAS.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:MATL IS VOLATILE & FLAMMABLE. TAKE PRECAUTIONS AGAINST FIRE. ABSORB MATL ON NONE FLAMMABLE ABSORBANT SUCH AS CLAY OR SAND. STOP LEAK IF POSSIBLE.

=====
Handling and Storage
=====

Handling and Storage Precautions:PROTECT AGAINST PHYSICAL DAMAGE.KEEP CONT CLOSED. AVOID FIRE HAZARDS. CONTR HAZARDOUS WHEN EMPTY(RETAIN,PRODUCT RESIDUE). OBSERVE HAZARD PRECAUTIONS.
Other Precautions:DO NOT STORE NEAR IGNITION SOURCES OR STRONG OXIDANTS SUCH AS LIQUID CHLORINE. WASH CONTAMINATED CLOTHING BEFORE REUSE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE
Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED
Protective Gloves:NONE
Eye Protection:OPTIONAL
Other Protective Equipment:NONE
Supplemental Safety and Health
MSDS DATED 2 JULY 1985 SAME MATL FURNISHED UNDER NSN 6850-01-174-0212

=====
Physical/Chemical Properties
=====

HCC:F4
Boiling Pt:B.P. Text:313-348F
Vapor Pres:36
Vapor Density:5.0
Spec Gravity:0.75
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BLACK LIQUID W/HYDROCARBON ODOR
Percent Volatiles by Volume:99

=====
Stability and Reactivity Dat

a =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: AVOID ANY IGNITION SOURCES. DO NOT SMOKE.

Hazardous Decomposition Products: FUMES; SMOKE & CARBON MONOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IAW ALL LOCAL, STATE & FEDERAL REGULATIONS. MAY BE INCINERATED.

Disclaimer (provided with this information by the compiling agencies):

This information is formulate

d for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.