View NSN Online: https://aerobasegroup.kr/nsn/9150-01-071-6222

TEXACO ING. -- 02316 MULTIGEAR LUBT EP SAE 80W-90 -- 9150-01-071-6222

Product ID:02316 MULTIGEAR LUBT EP SAE 80W-90 MSDS Date:01/01/1987 FSC:9150 NIIN:01-071-6222 MSDS Number: BGKKY === Responsible Party === Company Name: TEXACO ING. Emergency Phone Num:914-831-3400 EX.204 CAGE:MO827 === Contractor Identification === **Company Name: TEXACO INC** Box:509 City:BEACON Sta te:NY ZIP:12508-0509 Country:US Phone:914-831-3400 CAGE:7B131 Company Name: TEXACO ING. CAGE:MO827

Ingred Name:SOLVENT-DEWAXED HEAVY PARAFFINIC PETROLEUM,CAS#64742-65-0 (TLV AS OIL MIST 5.0 MG/CUM) Fraction by Wt: 57.5% ACGIH TLV:5MG/CUM(OILMIST

Ingred Name:HYDROTREATED C25 BRIGHT STOCK BASED LUBRICATING OIL,CAS#72623-83-7 (TLV AS OIL MIST) Fraction by Wt: 42.5% ACGIH TLV:5MG/CUM(OILMIST

Ingred Name: ADDITIVE (PACKAGE

CONTAINING BORON,P AND SULFUL Fraction by Wt: 7.5% ACGIH TLV:NOT SPECIFIED

| ====================================== |
|--|
| Effects of Overexposure:EYES:SL TO MOD IRRITATION;SKIN:IRRIT,REDNESS EDEMA OR DRYING OF SKIN;MAY IRRITATE RESPIRATORY TRACT. |
| ====================================== |
| First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FO R EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE. |
| ====================================== |
| Flash Point:360F/182C (COC) Extinguishing Media:WATER SPRAY,DRY CHEMICAL,FOAM,CO*2,FOAM Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN CONFINED AREA. Unusual Fire/Explosion Hazard:NONE NOTED |
| ====================================== |
| Spill Release Procedures:USE PROPER PERSONAL PROTECTION;WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP AND RECOVER FOR PROPER DISPOSAL. |
| ====================================== |
| Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA;KEEP AWAY FROM HEAT,OPEN FLAME;KEEP CONTAINER CLOSED WHEN NOT IN USE. |
| Other Precautions: AVOID CONTACT WITH SKIN, EYES AND CLOTHES; WASH THOROUGHLY AFTER EACH USE. DO NOT BREATHE VAPORS/MIST; DO NOT USE CONTAMINATED CLOTHES. |

======== Exposure Controls/Personal Protection ==

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF > TLV Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION Protective Gloves:NEOPRENE Eye Protection:SAFETY/CHEM GOGGLES Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION Supplemental Safety and Health MSDS DATED:04/16/86.

HCC:V6 Spec Gravity:0.9030 Solubility in Wa ter:NEGLIGIBLE Appearance and Odor:RED,GREEN BLOOM

Stability Indicator/Materials to Avoid:YES NONE NOTED Stability Condition to Avoid:HEAT,OPEN FLAMES Hazardous Decomposition Products:CO,CO*2,ALDEHYDE,KETONE,COMBUSTION PRODUCTS OF N,S.

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Discl

aimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.