

PITTSBURGH PENN OIL CO ///SEE SUPPLM. DATA -- ATF FA -- 9150-01-092-9755

=====
Product Identification
=====

Product ID:ATF FA

MSDS Date:01/01/1987

FSC:9150

NIIN:01-092-9755

MSDS Number: BGLNP

=== Responsible Party ===

Company Name:PITTSBURGH PENN OIL CO ///SEE SUPPLM. DATA

Address:RT 28,OLD FREEPORT ROAD

Box:296

City:CREIGHTON

State:PA

ZIP:15030

Country:US

Info Phone Num:412-441-8220

Emergency Ph

one Num:412-441-8220

CAGE:OO241

=== Contractor Identification ===

Company Name:PITTSBURGH PENN OIL CO ///SEE SUPPLM. DATA

Address:RT 28,OLD FREEPORT ROAD

Box:296

City:CREIGHTON

State:PA

ZIP:15030

Country:US

Phone:412-441-8220

CAGE:OO241

Company Name:WORLD AUTOMOTIVE TRANSPORT SUPPLIES INC

Address:918 PARK AVE SUITE 101

Box:City:PITTSBURGH

State:PA

ZIP:15234-2120

Country:US

Phone:412-343-1335

CAGE:1EV56

=====
Composition/Information on Ingredients
=====

Ingred Name:DISTILLATES

,SOLVENT-DEWAXED LIGHT NAPHTHENIC

CAS:64742-65-0

Fraction by Wt: >60%.

OSHA PEL:5 MG/CUM (OIL MIST)

ACGIH TLV:5 MG/CUM

Ingred Name:MFR'S MSDS STATES "SPECIFIC CHEMICAL IDENTITY HAS BEEN WITHHELD AS A TRADE SECRET".

RTECS #:9999999ZZ

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:EYES: CAN CAUSE MODERATE IRRITATION, REDNESS, TEARING;
SKIN: CAN CAUSE SLIGHT IRRITATION; INGEST: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA; INHAL: MIST CAN CAUSE DAMAGE TO NA SAL & RESPIRATORY PASSAGES.

=====
===== First Aid Measures =====

First Aid:EYES:FLUSH W/LARGE AMOUNTS OF WATER,LIFTING UPPER & LOWER LIDS OCCASIONALLY,GET MEDICAL ATTN; SKIN:THOROUGHLY WASH EXPOSED AREA W/SOAP & WATER.REMOVE CONTAMINATED CLOTHING.LAUNDER CONTAMINATED CLOTHIN G BEFORE REUSE; INGEST:I MMEDIATELY DRINK(2) GLASSES OF H2O & INDUCE VOMITING W/EITHER IPECAC SYRUP OR USING FINGER.NOTHING TO UNCONSC. PERSON-GET MED. ATTN; INHAL:REMOVE PARTY TO FRESH AIR!!

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:390F/198.9C
Upper Limits:1.1%
Extinguishing Media:REGULAR FOAM OR CARBON DIOXIDE OR DRY CHEMICAL
Fire Fighting Procedures:WEAR SELF-CONTND BRTHNG APPAR W/FULL FACEPIECE OPERATED IN PRESSURE-DEMAND/POSITIVE PRESS URE MODE; WATER OR FOAM MAY CAUSE FROTHING ESPEC. IF SPRAYED INTO CONTN
Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SM.SPILL:ABSORB LIQ. ON PAPER,VERMICULITE,/OTHER INERT MATERIAL,& TRANSFER TO HOOD;
LARGE:ELIMINATE ALL IGNITION SOURCES.EXCLUDE FROM SPILL AREA,PEOPLE W/O

PROTECTIVE EQUIP. STOP SPILL,DIKE,PUMP LIQUID TO SALVAGE TANK.PREVENT RUN-OFF TO WATERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AREA.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV EXCEEDED, USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. USE RESPIRATOR FOR OIL MIST; UP TO 50 MG/CUM: SUPPLIED AIR RESPIRATOR OR/

SELF-CONTAINED BREATHING APPARATUS/ AIR-PURIFYING RESP. W/HI-EFF.F.

Ventilation:PROVIDE SUFFICIENT MECHANICAL(GENERAL AND/OR LOCAL EXHAUST) VENTIL. TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:WEAR RESISTANT TYPE SUCH AS: NEOPRENE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:WEAR IMPERVIOUS CLOTHING & BOOTS TO PREVENT REPEATED OR PROLONGED SKIN CONTACT.

Supplemental Safety and Health

PITTSBURGH PENN BUYS PRODUCT FROM ASHLAND OIL & RECEIVES ASHLAND'S MSD

S. MSDS RECEIVED BY THIS OFFICE APPEARS TO BE A COPY OF ASHLAND'S MSDS W/ALL REFERENCE TO ASHLAND REMOVED- EXCEPT FOR AN EMERGENCY TELEPHONE NO. STAMPED ON THE MSDS; PITTSBURGH PENN. NAME & ADDRESS ON THE MSDS WE RECEIVED (DGSC-SLM).

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>425F/218C

Vapor Pres:5 MM @68F

Vapor Density:>1.

Spec Gravity:0.88

Viscosity:7 CS @ 212F

Evaporation Rate & Reference:SLOWER THAN ETHER

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HI-TEMPERATURES

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON DIOXIDE & CARBON MONOXIDE, PHOSPHOROUS COMPOUNDS, NITROGEN COMPOUNDS, ZINC OXIDE, ETC.

=====
===== Disposal Considerations =====

Waste Disposal Methods:SM. SPILL:ALLOW VOLATILE PORTION TO EVAPORATE IN HOOD

. ALLOW SUFFICIENT TIME FOR VAPORS TO CLEAR HOOD DUCT WORK.
DISPOSE OF REMAINING MATERIAL IAW APPLICABLE REGS; LARGE
SPILL:DESTROY BY LIQUID INCINE RATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizi
ng this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.