

MAGNOLIA PLASTICS, INC -- MAGNOBOND, PART A, 8388-3 -- 8040-01-102-2098

=====
Product Identification
=====

Product ID:MAGNOBOND, PART A, 8388-3

MSDS Date:08/02/1985

FSC:8040

NIIN:01-102-2098

MSDS Number: BGLWW

=== Responsible Party ===

Company Name:MAGNOLIA PLASTICS, INC

Address:5547 PEACHTREE INDUSTRIAL BOULEVARD

City:CHAMBEE

State:GA

ZIP:30341

Info Phone Num:(404) 451-2777

Emergency Phone Num:(

404) 451-2777

CAGE:22121

=== Contractor Identification ===

Company Name:MAGNOLIA PLASTICS INC

Address:5547 PEACHTREE INDUSTRIAL BLVD

Box:City:CHAMBLEE

State:GA

ZIP:30341-2234

Country:US

Phone:(770) 451-2777/(800) 457-4280

CAGE:22121

=====
Composition/Information on Ingredients
=====

Ingred Name:EPOXY RESIN (MULTIFUNCTIONAL & POLYFUNCTIONAL)

Fraction by Wt: 40-60%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

estion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NOT LIKELY TO PRODUCE

ADVERSE EFFECT DUE TO LOW VOLATILITY. INGESTION: LOW ORDER OF ORAL

TOXIITY. SKIN: NOT LIKELY TO BE ABSORBED THROUGH SKIN IN TOXIC

AMOUNTS. EYE: MODERATELY IRRITATING. SKIN: MODERATELY IRRITATING.

MAY CAUSESENSITIZATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:MODERATELY IRRITATING TO SKIN & EYES. POSSIBLE

SKIN SENSITIZER. PRE-E

EXISTING SKIN & EYES DISORDERS MAY BE AGGRAVATED.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN & EYES DISORDERS MAY BE AGGRAVATED.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINS HOLDING EYELIDS OPEN. GET MED ATT. SKIN: REMOVE CONTAMINATED CLOTHING. WASH W/SOAP & WATER. LAUNDER CLOTHING PRIOR TO RE-USE. INHALATION: REMOVE VICTIM TO FRESH AIR. ADMINISTER OXYGEN IF NECESSARY. INGESTION: DON'T INDUCE VOMITING. GIVE LARGE DOSES OF WATER. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F

Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:AVOID BREATHING SMOKE. IN CONFINED AREAS, FULL FIRE FIGHTING EQUIPMENT INCLUDING NIOSH APPROVED SCBA. COOL FIRE EXPOSED CONTAINERS WITH WATER.

Unusual Fire/Explosion Hazard:AUTOCATALYTIC POLYMERIZATION AT ABOUT 250F. DON'T USE A BAND HEATER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:AVOID CONTACT WITH LIQUID & VAPORS. WIPE WITH A CLOTH OR COLLECT ON ABSORBENT MATERIAL. LARGE SPILLS: DIKE & CONTAIN. PUMP OR SHOVEL INTO SALVAGE VESSELS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA IN TIGHTLY CLOSED CONTAINERS. AVOID CONTACT WITH SKIN & EYES. USE WITH ADEQUATE VENTILATION. USE GOOD HYGIENE PRACTICES.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:PROVIDE LOCAL EXHAUST & MECHANICAL VENTILATION TO KEEP 250F

Vapor Pres:NIL

Vapor Density:>1

Spec Gravity:1.40

Evaporation Rate & Reference:(BUTYL ACETATE = 1):