View NSN Online: https://aerobasegroup.kr/nsn/6850-01-106-7671

TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC -- TRITON I ACTIVATOR SOLUTION 6850-01-106-7671 Product ID:TRITON I ACTIVATOR SOLUTION MSDS Date:01/01/1987 FSC:6850 NIIN:01-106-7671 MSDS Number: BGMDJ === Responsible Party === Company Name: TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC Address:331 N OAK ST Box:398 City:OWEN State:WI ZIP:54460 Country:US **Emergency Pho** ne Num:201-647-1040 CAGE:MO933 === Contractor Identification === **Company Name: TELEDYNE INC** Address:150 MT BETHEL ROAD Box:City:WARREN State:NJ ZIP:07060-5147 Country:US CAGE:23428 Company Name: TELEDYNE ROTOLITE - SUBSIDIARY TELEDYNE INC Address:331 N OAK ST Box:398 City:OWEN State:WI ZIP:54460 Country:US CAGE:MO933 Ingred Name:ETHANOLAMINE

CAS:141-43-5 RTECS #:KJ5775000 Fraction by Wt: UNK OSHA PEL:3 PPM/6 STEL ACGIH TLV:3 PP M/6 STEL; 9192

Ingred Name:DIPROPYLENE GLYCOL,1,1'-OXYDI-2-PROPANOL CAS:110-98-5 RTECS #:UB8785000 Fraction by Wt: UNK

Health Hazards Acute and Chronic:CONTACT WITH EYES CAUSES BURNS. SKIN CONTACT MAY CAUSE IRRITATION. BREATHING OF VAPORS MAY CAUSE COUGHING AND DISCOMFORT IN NOSE,THROAT AND CHEST. Medical Cond Aggravated by Exposure:MANUFACTURER DID NOT SPECIFY.

First Aid:IMMEDIATELY FLUSH SKIN & EYE CONTACT W/PLENTY OF WATER FOR AT LEAST 15 MINUTES.GET MEDICAL CARE FOR EYES.

Flash Point:200F/280F COC Lower Limits:5/1 Upper Limits:17/9 Extinguishing Media:CO*2 OR DRY CHEMICAL Fire Fighting Procedures:DILUTION OF BURNING LIQUID WITH WATER WILL REDUCE FLAME INT. Unusual Fire/Explosion Hazard:WIL BURN;MAY EXPLODE;RUN OFF MAY POLLUTE/CREATE EXPLOSV FIRE HAZARD

Spill Release Procedures: FLUSH WITH LARGE VOLUMES OF WATER.

Handling and Storage Precautions:WARNING:STRONG ALKALINE SOLUTION.HARMFUL IF SWALLOWED,AVOID CONTACT WITH EYES,SKIN,OR CLOTHING.IN CASE OF CONTACT WITH EYES OR SKIN FLUSH W/H*20-15MIN Other Precautions:FOR EYES GET MEDICAL ATTENTION.

======= Exposure Controls/Personal Protection =

==================

Respiratory Protection:NONE REQD. Ventilation:LOCAL EXHAUST & MECHANICAL IS RECOMMENDED. Protective Gloves:RUBBER Eye Protection:GOGGLES Other Protective Equipment:EYE BATH & SAFETY SHOWER Work Hygienic Practices:WASH HANDS THOROUGHLY BEFORE EATING,SMOKING,USING SANITARY FACILITIES. Supplemental Safety and Health UPDATE PER UNDATED MSDS OSHA FORM 20 RECEIVED 8JAN88.

HCC:N1 Boiling Pt:B.P. Text:339F/451 Vapor Pres: