

MAGNAFLUX CORPORATION -- ZL-27A ZYGLO PENETRANT -- 6850-01-117-2971

=====  
Product Identification  
=====

Product ID:ZL-27A ZYGLO PENETRANT  
MSDS Date:06/04/1987  
FSC:6850  
NIIN:01-117-2971  
MSDS Number: BGMMY  
=== Responsible Party ===  
Company Name:MAGNAFLUX CORPORATION  
Address:7300 W. LAWRENCE AVENUE  
City:CHICAGO  
State:IL  
ZIP:60656-3504  
Country:US  
Info Phone Num:312-867-8000  
Emergency Phone Num:312-867-8000  
Preparer's Name:BRUCE C. GRAHAM  
CAGE:37676  
=== Contractor Identification ===  
Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV  
Address:3624 WEST LAKE AVENUE  
Box:City:GLENVIEW  
State:IL  
ZIP:60025  
Country:US  
Phone:847-657-5300/  
CAGE:37676

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DISTILLATES,(PETROLEUM)HYDROTREATED MIDDLE  
CAS:64742-46-7  
RTECS #:JN9379645  
Fraction by Wt: 10.0%

Ingred Name:KEROSENE  
CAS:8008-20-6  
RTECS #:OA5500000  
Fraction by Wt: 05.0%

A

CGIH TLV:100MG/CUM

Ingred Name:DISTILATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER  
RESIDUE,LOW BOILING

CAS:68477-31-6

Fraction by Wt: 25.0%

Ingred Name:UNIDENTIFIED COMPONENTS

Fraction by Wt: 60.0%

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATES EYES,MILDLY.

Effects of Overexposure:INHALATION:SPRAY MIST MAY IRRITATE TO BREATHING  
PASSAGES; EYES:LIQUID CONTACT MA

Y CAUSE IRRITATION; SKIN:SOLVENT IN

THE PRODUCT MAY IRRITATE SKIN; INGESTION:NOT NOTED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NOT STATED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE  
OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING  
WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN;  
EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS

AMOUNT OF RUNNING

WATER,AND GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:PMCC

Flash Point:>200F/>93C

Extinguishing Media:CARBON DIOXIDE,FOAM.

Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT  
SPRAY ON BURNING PRODUCT.

Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC  
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

=====  
===== Accidental Release Measures =====

===

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBENT.T.TRANSFER WASTE MATL IN SALVAGE TANKS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP

CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A RESPIRATOR WITH CHEMICAL CARTRIDGE. IN CONFINED AREAS,WEAR A FULL MASK WITH SEPARATE AIR SUPPLY.

Ventilation:GENERAL VENTILATION TO KEEP BELOW 350PPM LIMIT.

Protective Gloves:NITRILE RUBBER GLOVES.

Eye Protection:FULL GOGGLES.WHEN SPRAYING OR POURING.

Other Protective Equipment:EITHER USE IN A SPRAY BOOTH OR NEXT TO AN EXHAUST VENT.

Work Hygienic Practices:AVOID SKIN CONTACT.WASH THOROUGHLY AFTER HANDLING OR USE.LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

NSN FOR TYPE I,METHOD B,LEVEL 3 MATERIAL OF MIL-I-25135D;ZL-27A

PENETRANT IS A QUALIFIED PRODUCT OF QPL-25135-15 FOR TYPE I,METH B,LEVL 3;THE QPL ALSO SPECIFIED THAT THIS PENETRANT MAY BE A PART OF KI T WITH SEVERAL QUAL

IFIED EMULSIFIERS FOR THE SAME AND/OR

OTHER TYPE,METHOD & LEVL SEE OTHER PNI FOR OTHER PENETRANT.

=====  
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:410F/210C

Vapor Pres:0.5 @100F

Vapor Density:>1.0

Spec Gravity:0.96

Solubility in Water:NEGLIGIBLE

Appearance and Odor:GREEN LIQUID WITH PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume:5.0%

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to

Avoid: YES

MFR STATED "NONE".

Stability Condition to Avoid: HEAT, HIGH TEMPERATURES.

Hazardous Decomposition Products: EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE), IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE, LOCAL REGULATIONS; IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER, PURIFY RINSINGS W/MAGNAFLU  
X WASTEWATER  
TREATMENT SYSTEM

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.