View NSN Online: https://aerobasegroup.com/nsn/9160-01-118-7105

BOEKEL INDUSTRIES INC -- MICRO WAX#2-600-5 -- 9160-01-118-7105

Product ID:MICRO WAX#2-600-5 MSDS Date:01/01/1987 FSC:9160 NIIN:01-118-7105 **MSDS Number: BGMPN** === Responsible Party === Company Name: BOEKEL INDUSTRIES INC Address:509 VINE ST City:PHILADELPHIA State:PA ZIP:19106-1002 Country:US Emergency Phone Num:215-223-2600 CAGE:07836 === Contractor Identificatio n === Company Name: BOEKEL INDUSTRIES INC Address:509 VINE ST Box:City:PHILADELPHIA State:PA ZIP:19106-1002 Country:US Phone:215-627-1611 CAGE:07836

Ingred Name:MICROCRYSTALLINE WAX CAS:8002-74-2 RTECS #:RV0350000 Fraction by Wt: 96% ACGIH TLV:2 MG/CUM

Ingred Name:MINERAL OIL Fraction by Wt: 4% ACGIH TLV:5 MG/CUM

Routes of Entry: Inhalation:NO Skin:NO Ing

estion	:NO

Effects of Overexposure:MAY SUFFER THERMAL BURNS WHEN HANDLING HOT WA
NO PROBLEM EXPECTED WITH UNHEATED SOLID WAX.

======================================
First Aid:TREAT FOR THERMAL BURNS TO HOT WAX IF MOLTEN WAX IS BEING HANDLED.
======================================
Flash Point Method:COC Flash Point:540F/282C Extinguishing Media:FOAM DRY CHEMICAL OR CO*2. Fire Fighting Procedures:AVOID CONTACT OF SKIN, EYES AND CLOTHING WITH HOT WAS. Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:SWEEP UP AND SCOOP UP AND PLACE IN NORMAL REFUSE OR IN CHEMICAL DISPOSAL AREA.
======================================
Handling and Storage Precautions:NONE REQUIRED UNLESS HANDLING HOT OR MOLTEN WAX.
======== Exposure Controls/Personal Protection ====================================
Respiratory Protection:NONE NO RMALLY.
Ventilation:GENERAL MECHANICAL Protective Gloves:NONE EXCEPT FOR HOT WAX. Eye Protection:NONE EXCEPT FOR HOT WAX. Supplemental Safety and Health
======================================
HCC:N1 Boiling Pt:B.P. Text:500F/260C Melt/Freeze Pt:M.P/F.P Text:176F/80C Vapor Pres:0.01 MMHG Vapor Density:1 Spec Gravity:0.93 Solubility in Water:INSOLUBLE Appearance and Odor:YELLOW-AMBER WAX OF LOW ORDER.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZIN AGENTS.

Waste Disposal Methods:DISPOSE OF SOLID IN WASTE DISPOSAL AREA. MAY MIX WAX WITH HYDROCARBON SOLVENTS AND BURN IN AN INCINERATOR UNDER CONTROLLED CONDITIONS TO MEET LOCAL ORDINANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Unite

d States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.