View NSN Online: https://aerobasegroup.com/nsn/6850-01-140-0288

## CHEMICAL COMMODITIES AGENCY, INC. -- NAVSEA PD 515-82-16 -- 6850-01-140-0288

Product ID:NAVSEA PD 515-82-16

MSDS Date:01/01/1985

FSC:6850

NIIN:01-140-0288

MSDS Number: BGNQM === Responsible Party ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

City:HIGHLAND

State:CA

ZIP:92346-2640 Country:US

Info Phone Num:714-864-2310

**Emergency Pho** 

ne Num:714-864-2310

CAGE:60777

=== Contractor Identification ===

Company Name: CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640 Country:US

Phone:909-864-2310

CAGE:60777

======= Composition/Information on Ingredients ========

Ingred Name:SOLVENTS(% WT >80%)

Fraction by Wt: 80.0%

Ingred Name: CARBON DIOXIDE

CAS:124-38-9

RTECS #:FF6400000 Fraction by Wt: 5.0% OSHA PEL:5000 PPM

ACGIH TLV:5000PPM/30000STEL;93

\_\_\_\_\_

Hazards Identification ==============
Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.
======================================
First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER. INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.
======================================
Flash Point:NONE Extinguishing Media:CO*2, FOAM, DRY CHEM.
========= Accidental Relea se Measures ====================================
Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. STOP LEAK. H*20 SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS LG SPILL:DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.
======================================
Handling and Storage Precautions:DO NOT STORE ABOVE 120F.KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEAT MAY CAUSE
BURSTING;STORE IN COOL,DRY WELL VENTILATD AREA Other Precautions:KEEP AWAY FROM CHILDREN;DO NOT PUNCTURE OR INCINERATE.
======= Exposure Controls/Personal Protection ========
Respiratory Protection:DUST/MIST RESPIR Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:AS REQUIRED Eye Protection:AS REQUIRED Supplemental Safety and Health MSDS UNDATED;ITEM IS PURCHASED IAW NAVSEA PD 515-82-16;CARBON DIOXIDE IS USED AS PROPELLENT LESS THAN 5%.
_

======================================
HCC:V2
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE
Stability Condition to Avoid:NONE  ==================================

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided wi

th this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.