

STANCHEM INC -- RED PLASTISOL -- 5970-01-163-6786

=====  
Product Identification  
=====

Product ID:RED PLASTISOL

MSDS Date:05/31/1989

FSC:5970

NIIN:01-163-6786

MSDS Number: BGPMPR

=== Responsible Party ===

Company Name:STANCHEM INC

Address:401 BERLIN ST

City:EAST BERLIN

State:CT

ZIP:06023-9706

Country:US

Info Phone Num:203-828-0571

Emergency Phone Num:203-828-0571

CAGE:78520

=== Contractor Identifica  
tion ===

Company Name:LIN-FASTENERS INC

Address:ROUTE 73

Box:City:BERLIN

State:NJ

ZIP:08009

Country:US

CAGE:4M357

Company Name:STANCHEM INC

Address:401 BERLIN ST

Box:City:EAST BERLIN

State:CT

ZIP:06023-9706

Country:US

Phone:203-828-0571

CAGE:78520

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIBASIC LEAD PHTHALATE

CAS:6838-85-3

Fraction by Wt: 0.5%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:50 MG/M3 (MFR)

Ingred Name:POLYVINYL CHLORIDE RESIN

CAS:9002-86-2

RT

ECS #:KV0350000  
Fraction by Wt: 53%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:1 PPM (8 HRS.) (MFR)

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE-INHALATION: NO ADVERSE EFFECTS.  
SKIN: IRRITATION, DERMATITIS. EYES: PRIMARY IRRITATION. CHRONIC-  
MAY CAUSE DERMATITIS.  
Effects of Overexposure:SKIN IRRITATION, DERMATITIS. PR  
IMARY EYE  
IRRITATION.  
Medical Cond Aggravated by Exposure:SINUS & DERMATITIS.

=====  
First Aid Measures  
=====

First Aid:FIRST AID-EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15  
MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER.  
REMOVE CONTAMINATED CLOTHING. INGESTION: DILUTE WITH CLEAR FLUID.  
GET MEDICAL ATTENTION OR POISON CONTROL CENTER.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:475F,246C  
Extinguishing Media:WATER SPRAY, CO2, FOAM/DRY CHEMICAL. WATER SPRAY  
MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS  
AWAY.  
Fire Fighting Procedures:FIGHT AS VOLATILE LIQUID FIRE. CLOSE  
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. WEAR  
SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE EQUIPMENTS.  
Unusual Fire/Explosion Hazard:MAY PRODUCE HYDROGEN CHLORIDE, CARBON  
DIOXIDE AND/OR CARBON MONOXIDE. PRODUCT FUSES AT 350 F.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:AVOID SOURCES OF IGNITION. STOP SPILL AT  
SOURCE. PLACE SPILLED MATERIAL IN DOT APPROVED CONTAINER AND BAKE  
FOR SOLIDIFICATION.  
Neutralizing Agent:NONE

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORAGE-AVOID EXPOSING PRODUCT TO HEAT  
ABOVE 150 F. STORE BELOW 90 F.  
Other Precautions:ADEQUATE OVEN VENTILATION, AVOID BREATHING FUMES  
WH

ILE BAKING. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED WHILE HANDLING THE MATERIAL BUT CAUTION WHEN BAKING.

Ventilation:LOCAL EXHAUST AS REQUIRED BY JOB CONDITIONS TO KEEP TLV BELOW ACCEPTABLE LIMITS.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:SAFETY SHOWER AND EYE BATH. INDUSTRIAL TYPE WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. DO NOT BREATHE VAPORS OR CONTACT WITH EYES, SKIN & CLOTHES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:450F,232C

Vapor Density:>1

Spec Gravity:10.1 LB/GAL

Evaporation Rate & Reference: