View NSN Online: https://aerobasegroup.kr/nsn/6750-01-169-1851

Product ID:156 6538, FIRST DEVL, PROC E-6 (SEE SUPPL DATA MSDS Date:07/08/1992 FSC:6750 NIIN:01-169-1851 Kit Part:Y **MSDS Number: BGPPW** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Nu m:716-477-3194 FOR MSDS : 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 55 - 60% Other REC Limits:NONE SPECIFIED

Ingred Name: POTASSIUM SULFITE

CAS:10117-38-1 Fraction by Wt: 10 - 15% Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM CARBONATE CAS:584-08-7 RTECS #:TS7750000 Fraction by Wt: 5 - 10% Other REC Limits:NONE SPECIFIED

Ingred Name:DIETHYLENE GLYCOL CAS:111-46-6 RTECS #:ID5950000 Fraction by Wt: 5 - 10% Other REC Limits:NONE SPECIFIED

Ingred Name:POTASSIUM HYDROQUINONE MONOSULFONATE CAS:21799-87-1 Fraction by Wt: 5 - 10% Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM CARBONATE CAS:497-19-8 RTECS #:VZ4050000 Fractio n by Wt: 1 - 5% Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE- INHALATION:LOW HAZARD FOR USUAL INDUSTRIAL HANDLING. EYES:MAY CAUSE TRANSIENT IRRITATION. SKIN:CAN CAUSE ALLERGIC REACTION. INGESTION:EXPECTED TO BE A LOW INGESTION HAZARD. CHRONIC-NONE KNOWN.
Effects of Overexposure:LOW
HAZARD FOR USUAL INDUSTRIAL HANDLING. MAY CAUSE TRANSIENT EYE IRRITATION. CAN CAUSE ALLERGIC SKIN REACTION. EXPECTED TO BE A LOW INGESTION HAZARD.
Medical Cond Aggravated by Exposure:NONE KNOWN.

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:WASH WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED:REMOVE TO FRESH AIR. ORAL:DRINK 1-2 GLASSES OF WATER. GET MED IC Flash Point:NONE

- Extinguishing Media:WATER SPRAY,CO2,"ALCOHOL" FOAM/DRY CHEMICAL. WATER MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.
- Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN & EYES. Unusual Fire/Explosion Hazard:FIRE/EXCESSIVE HEAT MAY CAUSE PRODUCTION
- OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====

Spill Release Procedures: FLUSH SMALL SPILL TO THE SEWER WITH LARGE AMOUNT OF WATER. ABSORB LARGE SPILL WITH INERT MATERIAL AND PLACE IN A CONTAINER FOR CHEMICAL WASTE. PREVENT RUNOFF FROM ENTERING DRAINS, SEWERS AND STREAMS.

Handling and Storage Precautions:STORAGE- KEEP FROM OXIDIZING MATERIALS. KEEP CONTAINER TIGHTLY CLOSED AND AWAY FROM ACIDS. Ot

her Precautions: AVOID BREATHING VAPORS OR MISTS. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. REMOVE CONTAMINATED CLOTHING PROMPTLY. KEEP OUT OF REACH OF C HILDREN.

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation: GOOD GENERAL VENTILATION IS SUFFICIENT FOR MOST CONDITIONS (10 ROOM VOLUMES PER HOUR).

Protective Gloves: IMPERVIOUS

Eye Protectio

n:SAFETY GLASSES WITH SIDE SHIELDS

Other Protective Equipment: EYE WASH STATION, QUICK DRENCH SHOWER AND IMPERVIOUS CLOTHING

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

KEY1:Z01;ITEM IS 9 PARTS KIT;IT CONSISTS OF DEVL(PART A&B),BLEACH(PART A&B),FIRST DEVL,FIXER,CONDITIONER,REVERSAL BATH AND STABILIZER;EFFECTIVE 12/27/82 KIT CAT #156 6538 WAS CHANGD TO 1

01

7433 THEN T O 106 3973; DURING 1985, KODAK AGAIN CHANGD TRADE NAME & CAT NO; SEE PNI J-O FOR NEW KIT; THIS IS: FIRST DEVELOPER, PROC E-6

HCC:B3 NRC/State Lic Num:NOT RELEVENT Boiling Pt:B.P. Text:>212F/>100C Vapor Pres:18 @ 68F Vapor Density:0.6 Spec Gravity:1.316 pH:9.9 Solubility in Water:COMPLETE Appearance and Odor:CLEAR AMBER SOLUTION; ODORLESS Percent Volatiles by Volume:55- 60

====== Stability and Rea

ctivity Data =================

Stability Indicator/Materials to Avoid:YES STRONG ACIDS, STRONG ALKALIES Stability Condition to Avoid:EXPOSURE TO HIGH HEAT Hazardous Decomposition Products:CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE AND SULFUR OXIDES

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agen cies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.