

D-A LUBRICANT CO,INC -- D-A HYDRATRANS 135 -- 9150-01-177-9438

=====
Product Identification
=====

Product ID:D-A HYDRATRANS 135

MSDS Date:11/11/1985

FSC:9150

NIIN:01-177-9438

MSDS Number: BGPVD

=== Responsible Party ===

Company Name:D-A LUBRICANT CO,INC

Address:1340 WEST 29TH STREET

City:INDIANAPOLIS

State:IN

ZIP:46208

Country:US

Emergency Phone Num:(317) 923-5321

CAGE:30719

=== Contractor Identi

fication ===

Company Name:D-A LUBRICANT CO INC SUB OF PREMIER INDUSTRIAL

Address:1340 W 29TH ST

Box:City:INDIANAPOLIS

State:IN

ZIP:46208-4943

Country:US

Phone:317-923-5321/216-391-8300 OTHER HRS

CAGE:30719

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM BASED LUBRICANT

ACGIH TLV:5MG/CUM(MIST)

Ingred Name:SOLVENT REFINED;HYDROTREATED PARAFFINIC BASE OIL

ACGIH TLV:5MG/CUM(MIST)

Ingred Name:ADDITIVES MIXTURE(AS DETERGENT,DISPERSANT,ANTIOXIDANT,AND

P

OLYMERIC

===== Hazards Identification =====

Effects of Overexposure:EYES:MAY CAUSE SLIGHT IRRIT;SKIN:MILD IRRIT ON REPEATD CONTACT;INHAL/INGEST:LOW TOXICITY

===== First Aid Measures =====

First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point:430F/221C (COC)
Lower Limits:1.0
Upper Limits:7.0
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:WHEN HEATED ABOVE FLASH PT,VAPOR RELEASED COULD CREATE AN EXPLOSIVE ATMOSPHERE.

===== Accidental Release Measures =====

Spill Release Procedures:RE
MOVE ALL SOURCES OF IGNITION AROUND SPILL
AREA. CLEAN UP SPILL AS SOON AS POSSIBLE.USE ABSORBENT SUCH AS CLAY OR DIATOMACEOUS EARTH TO CLEAN UP SPILL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALL,UNLESS OIL MIST ABOVE TLV.
Ventilation:NONE
Protective Gloves:IMPERVIOUS.
Eye Protection:GOGGLES/FACE SHI

ELD
Supplemental Safety and Health
MSDS FROM D-A LUBRICANT CO DATED:11/11/85.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>550F/>288C
Vapor Density:>8
Spec Gravity:0.879
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT BROWN LIQUID,OIL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:AVOID EXCESSIVE HEAT.
Hazardous Decomposition Products:CO,OXIDES OF
CALCIUM,ZINC,PHOSPHOROUS,&H₂S.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF CONTAMINATED MATL IN AN APPROVED
DISPOSAL SITE. WASTE OIL CAN BE DISPOSED OF BY CONTROLLED
INCINERATION OR OTHER APPROVED METHOD.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.