

EASTMAN KODAK COMPANY -- 153 2753 FLEXICOLOR DEVELOPER REPLENISHER, PART C --  
6750-01-178-4421

===== Product Identification =====

Product ID:153 2753 FLEXICOLOR DEVELOPER REPLENISHER, PART C

MSDS Date:06/22/1994

FSC:6750

NIIN:01-178-4421

MSDS Number: BGPVL

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone N

um:716-477-3194 MSDS :800- 242-2424

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

===== Composition/Informati

on on Ingredients =====

Ingred Name:4-(N-ETHYL-N-2-HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE  
SULFATE  
CAS:25646-77-9  
RTECS #:KJ6477000  
Fraction by Wt: 40-45%

Ingred Name:SODIUM METABISULFITE  
CAS:7681-57-4  
RTECS #:UX8225000  
Fraction by Wt: 1-5%  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9192

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 50-55%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
He

alth Hazards Acute and Chronic:PRODUCT CAUSES IRRITATION AND MAY  
CAUSE KIDNEY DAMAGE IF INGESTED OR ABSORBED THROUGH SKIN. PRODUCT  
(ESPECIALLY AS THE CONCENTRATE) RELEASES SULFUR DIOXIDE,A  
RESPIRATORY IRRITANT WITH A TLV OF 2 PPM.

Effects of Overexposure:EYE:IRRITATION. SKIN:IRRITATION AND/OR POSSIBLE  
ALLERGIC REACTION. INHALED:IRRITATION. INGESTED:G/I  
DISTRESS/IRRITATION.

Medical Cond Aggravated by Exposure:NONE LISTED BY MFR.

===== First Aid Measures ==  
=====

First Aid:EYE:FLUSH WITH WATER,GET MEDICAL ATTENTION. SKIN:FLUSH WITH  
WATER.GET MEDICAL ATTENTION IF IRRITATION PERSISTS OR ALLERGY  
APPEARS. INHALED:REMOVE TO FRESH AIR.GET MEDICAL ATTENTION IF  
SYMPTOMS PERSIST S. INGESTED:RINSE MOUTH,GIVE 2 GLASSES OF  
WATER,INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. NOTHING BY  
MOUTH IF UNCONSCIOUS.

===== Fire Fighting Measures =====

Flash Point:NONE  
Lower Limits:NONE  
Upper Lim

its:NONE

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE,  
"ALCOHOL" FOAM

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
PROTECTIVE CLOTHING

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE  
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS

===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO DRAIN WITH LARGE AMOUNT OF WATER.

Neutralizing Agent:NONE LISTED BY MFR.

=====

Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED  
AREA. PROTECT FROM PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP  
CONTAINERS TIGHTLY CLOSED

Other Precautions:AVOID CONTACT WITH MINERAL ACIDS & ALKALI. KEEP FROM  
CONTACT WITH OXIDIZING MATL. AVOID BREATHING VAPORS. USE W/ ADEQUATE  
VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A NI  
OSH APPROVD ACID GAS RESP SHOULD BE WORN IF  
NEEDED

Ventilation:GOOD GENERAL VENTILATION OR LOCAL EXHAUST TO CONTROL TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR  
PROLONGED CONTACT.

Supplemental Safety and Health

KEY1: C1. THIS IS A THREE PART KIT.

===== Physical/Chemical Properties =====

HCC:C2

Boiling Pt:B.P. Text:212F, 100C

Melt/Freeze Pt:M.P/F.P Text:NOT GIVEN

Vapor

Pres:18  
Vapor Density:0.6  
Spec Gravity:1.18  
pH:2.12  
Evaporation Rate & Reference:NOT GIVEN  
Solubility in Water:COMPLETE  
Appearance and Odor:REDDISH-BROWN SOLUTION, SULFUR DIOXIDE ODOR  
Percent Volatiles by Volume:55 %

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID STRONG OXIDIZERS, STRONG BASES  
Stability Condition to Avoid:MOISTURE  
Hazardous Decomposition Products:COMBUSTION MAY PRODUCE OXIDES OF  
CARBON,SULFUR,& NITRO  
GEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document s  
ould seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.