

INTEX CHEMICAL INC. -- INTEX 8758(ALKALINE CLEANER) -- 6850-01-184-7453

=====
Product Identification
=====

Product ID:INTEX 8758(ALKALINE CLEANER)

MSDS Date:01/01/1987

FSC:6850

NIIN:01-184-7453

MSDS Number: BGQBB

=== Responsible Party ===

Company Name:INTEX CHEMICAL INC.

Emergency Phone Num:803-242-6152

CAGE:78304

=== Contractor Identification ===

Company Name:INTEX CHEMICAL INC

Address:122 EDINB

URG CT

Box:6648

City:GREENVILLE

State:SC

ZIP:29606-6648

Country:US

Phone:803-879-7100 OR 803-297-4246

CAGE:78304

=====
Composition/Information on Ingredients
=====

Ingred Name:SODIUM HYDROXIDE (SARA III)

CAS:1310-73-2

RTECS #:WB4900000

Fraction by Wt: 0.1%

OSHA PEL:2 MG/M3

ACGIH TLV:C 2 MG/M3; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 5%.

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name

:MFR. STATES "NO OTHER HAZARDOUS INGRED AS LISTED IN
29CFR1910.1000 TO 1910.1200."

RTECS #:9999999ZZ

Ingred Name:PER PARAG. 3.2 OF SPEC "CMPS. SHALL NOT CONTAIN ANY
PHOSPHATES,ABRASIVES,CHROMATES,PHENOL

RTECS #:9999999ZZ

Fraction by Wt: 0.0%

Ingred Name:CRESOLS,HEAVY METALS OR ANY INERT FILLERS SUCH AS
NACL,UREA,NA*2SO*4,NO*3,NO*2,SUCROSES"

RTECS #:9999999ZZ

Fraction by Wt: 0.0%

=====
Hazards Identification
=====

Effects of Overexposure:EYES:IRRI
TATES; SKIN:MAY IRRITATE W/REPEATED
EXPOSURE; INHAL:MAY IRRITATE IF EXPOSED TO MIST.

=====
First Aid Measures
=====

First Aid:EYES:FLUSH W/WATER FOR 15 MIN.-GET MEDICAL AID;SKIN:FLUSH
W/WATER FOR 15 MIN.,REMOVE CONTAMINATED CLOTHING-CONSULT MEDICAL IF
IRRITATION PERSISTS; INHAL:REMOVE TO FRESH AIR,GIVE CPR/O*2 AS
SITUATION D ICTATES.GET MEDICAL AID; INGEST:DILUTE W/H*2O.

=====
Fire Fighting Measures
=====

Flash Point:>200F/>93.3C
Extinguishing Media:WATER,CO*2,FOAM
Fire Fighting Procedures:MOVE CONT FROM AREA. USE H*2O TO COOL EXPOSED
CONT.
Unusual Fire/Explosion Hazard:CONTAINER MAY RUPTURE IN HEAT OF FIRE.

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE EQUIPM.; FOR SM.
SPILL: MOP DRY & FLUSH RESIDUE TO AN AUTHORIZED DRAIN SITE. FOR
LARGE SPILL: STOP LEAK, DIKE FAR AHEAD OF SPILL, COLLECT INTO
AUTHORIZED

