

AIRCO DIV. OF "THE BOC GROUP" INC. -- MAPP GAS(LIQFD. PETRLM GAS W/METHYL-ACETY-P --
3439-01-195-8717

===== Product Identification =====

Product ID:MAPP GAS(LIQFD. PETRLM GAS W/METHYL-ACETY-P

MSDS Date:11/01/1986

FSC:3439

NIIN:01-195-8717

MSDS Number: BGQHT

=== Responsible Party ===

Company Name:AIRCO DIV. OF "THE BOC GROUP" INC.

Address:575 MOUNTAIN AVE.

City:MURRAY HILL

State:NJ

ZIP:07974

Countr

y:US

Info Phone Num:201-464-8100

Emergency Phone Num:201-464-8100

CAGE:NO185

=== Contractor Identification ===

Company Name:AIRCO DIV. OF "THE BOC GROUP" INC.

Address:575 MOUNTAIN AVE.

Box:City:MURRAY HILL

State:NJ

ZIP:07974

Country:US

Phone:201-464-8100

CAGE:NO185

Company Name:DIV OF THE BOC GROUP INC AIRCO INC

Address:575 MOUNTAIN AVENUE

Box:City:MURRAY HILL

State:NJ

ZIP:07974

Country:US

Phone:908-665-2400

CAGE:6S493

Company Name:UNIWELD PRODUCTS, INC

Address:2850 RAVENSWOOD RD

Box:8427

City:F

ORT LAUDERDALE
State:FL
ZIP:33310
Country:US
Phone:954-584-2000
CAGE:17941

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ACETYLENE (PROPYNE)
CAS:74-99-7
RTECS #:UK4250000
Fraction by Wt: 44%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:LPG (LIQUEFIED PETROLEUM GAS)
CAS:68476-85-7
RTECS #:SE7545000
Fraction by Wt: 56%.
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192

Ingred Name:PROPADIENE(ONE OF THE CONSTITUENTS OF THE METHYL
ACETYLENE-PROPADIENE MIXTURE)
CAS:463-49-0

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:A CENTRAL NERVOUS SYSTEM DEPRESSANT &
IRRITANT; BEING A SIMPLE ASPHYXIAN, INHALATION AT HI-CONC. SO AS
TO EXCLUDE AN ADEQUATE SUPPLY OF OXYGEN TO THE LUNGS WILL CAUSE
UNCONSCIOUSNESS, & POSSIBLE DEATH; REPEATED EXPOSURE TO TOLERABLE
LEVELS HAS NOT SHOWN DELIRIOUS EFFECTS.
Effects of Overexposure:INHAL: A CNS DEPRESSANT & IRRITANT; LOW CONC.
WILL CAUSE EXCITEMENT & DISORIENTATION; EYE/SKIN: CONTACT W/LIQUID
WILL CAUSE FROSTBITE, IRRITATION, OR BLINDNESS.
Medical Cond Aggravated by Exposure:NONE LISTED.

=====
First Aid Measures
=====

First Aid:INHAL: ESCORT CONSCIOUS PARTIES TO AN UNCONTAMINATED AREA &
INHALE FRESH AIR. QUICK REMOVAL FROM THE CONTAMINATED AREA IS MOST
IMPORTANT.

FOR UNCONSCIOUS INDIVIDUAL GIVE CPR/O2 AS SITUATION
DICTATES.; SKIN FOR DERMAL CONTACT OR FROSTBITE, REMOVE
CONTAMINATED CLOTHING & FLUSH AFFECTED AREAS W/LUKEWARM WATER. DO
NOT USE HOT WATER.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:144F/62.2C
Autoignition Temp:Autoignition Temp Text:850F
Lower Limits:3.0
Upper Limits:11.0
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM
Fire Fighting Procedures:DO NOT EXTINGUISH.KEEP
CYLINDER COOL W/WATER
FOG.IF FLAME EXTINGUISHED,REMOVE ALL IGNITION SOURCES & ALLOW
CONTENTS TO VENT; INCREASE VENTIL.TO PRVNT FLAM MX.
Unusual Fire/Explosion Hazard:GAS IS HEAVIER THAN AIR & MAY TRAVEL A
CONSIDERABLE DISTANCE TO AN IGNITION SOURCE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL PERSONNEL FROM AFFECTED AREA. USE
APPROPRIATE PROTECTIVE EQUIPMENT. IF LEAK IS IN USER'S EQUIPMENT,BE
CERTAIN TO PURGE PIP
ING W/ AN INERT GAS PRIOR TO ATTEMPTING
REPAIRS. IF LEAK IS IN CO NTAINER OR CONTAINER VALVE,CONTACT
CLOSEST SUPPLIR

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY IN WELL VENTILATED AREA &
PROTECT FROM PHYSICAL DAMAGE. STORE IN COOL,DRY,WELL VENTILATED
AREA OF NON-COMBUSTIBLE CONSTRUCTION.
Other Precautions:STORAGE TEMPERATURE IS NOT TO EXCEED 130F/54C.
EARTH-GROUND & BOND ALL LINES & EQUIPMENT ASSOCIATED W/FUE
L GAS
SYSTEM. THIS FUEL GAS SHOULD NOT BE HANDLED OR USED IN METALS WHICH
FORM ACETYLIDES(EG. C U, AG, MG OR THEIR ALLOYS).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. DO NOT ENTER AREA OF HIGH
"MAPP" CONCENTRATION UNTIL FIRST PURGING WITH INERT GAS & THEN
VENTILATING WITH AIR.
Ventilation:PROVIDE LOCAL EXHAUST OR MECHANICAL VENTILATION IF WELDING
OR CUTTING IN CONFINED AREAS WHERE TLV'S MAY BE EXCEEDED.

Protective Gloves:LEATHER GLOVES WHEN WELDING,CUTTING/BRAZ
Eye Protection:SAFETY GLASSES W/FILTER LENS #4 OR MORE
Other Protective Equipment:APPROPRIATE TYPE APRON.
Supplemental Safety and Health
16 OZ "MAPP GAS" CYLINDER IS PART OF KIT (MKT-4L); UNIWELD OBTAINS
"MAPP GAS" FROM THE MFR. CITED ON THE MSDS.

===== Physical/Chemical Properties =====

HCC:G2
Boiling Pt:B.P. Text:-54 TO -10F
Melt/Freeze Pt:M.P/F.P Text:-184F/-120C
Vapor Pres:97PSIG:70F
Vapor Density:0.
11LB/FT3
Spec Gravity:1.48(G);0.571(L
Solubility in Water:SLIGHT
Appearance and Odor:COLORLESS GAS W/CHARACTERISTIC UNPLEASANT ODOR.
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NATURAL RUBBER; COPPER ALLOY >65% COPPER; SILVER; MERCURY; HALOGENS;
ACIDS; METALLIC SODIUM,POTASSIUM,POTAS. PERMANGANT
Stability Condition to Avoid:MFR CITES NONE; IGNITION SOURCES,
HI-TEMPERATURES
Hazardous Deco
mposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT ATTEMPT TO DISPOSE OF WASTE OR UNUSED
QUANTITIES. RETURN IN THE SHIPPING CONTAINER PROPERLY LABELED, W/
VALVE PROTECTION CAP IN PLACE TO SUPPLIER FOR PROPER DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner wh
atsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.