

EASTMAN KODAK COMPANY -- 186 2176,EKTAPRNT 2 BLEACH-FIX, PART A -- 6750-01-214-4621

=====  
Product Identification  
=====

Product ID:186 2176,EKTAPRNT 2 BLEACH-FIX, PART A

MSDS Date:02/08/1995

FSC:6750

NIIN:01-214-4621

Kit Part:Y

MSDS Number: BGQSK

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-

5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====  
Composition/Information on Ingredients  
=====

=

Ingred Name:AMMONIUM THIOSULFATE  
CAS:7783-18-8  
RTECS #:XN6465000  
Fraction by Wt: 45-50%  
Other REC Limits:NONE SPECIFIED

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 40-45%  
Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM BISULFITE (SARA III)  
CAS:7631-90-5  
RTECS #:VZ2000000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BISULFITE (SARA III)  
CAS:10192-30-0  
RTE  
CS #:WT3595000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM ACETATE (SARA III)  
CAS:631-61-8  
RTECS #:AF3675000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:TLV: SODIUM BISULFITE: 5 MG/M3  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO

OSHA:NO

Health Hazards Acute and Chronic:INHALATION-LOW HAZARD FOR RECOMMENDED HANDLING. EYES-NO SPECIFIC HAZARD KNOWN. MAY CAUSE TRANSIENT IRRITATION. SKIN-LOW HAZARD FOR RECOMMENDED HANDLING. INGESTION-EXPECTED TO BE A LOW INGESTION HAZARD .

Explanation of Carcinogenicity:NOT CARCINOGENIC.

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:INHALATION-IF SYMPTOMATIC, MOVE TO FRESH AIR. TREAT SYMPTOMATICALLY. GET MEDICAL AID. EYES-ANY MATERIAL THAT CONTACTS THE EYE SHOULD BE WASHED OUT IMMEDIATELY WITH WATER. GET MEDICAL AID. SKIN-WASH WITH SOAP & WATER. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION-DRINK 1-2 GLASSES OF WATER. SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE

Lower

Limits:NOT RELEVANT

Upper Limits:NOT RELEVANT

Extinguishing Media:USE APPROPRIATE AGENT FOR ADJACENT FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. HAZARDOUS DECOMPOSITION PRODUCTS MAY BE FORMED.

Unusual Fire/Explosion Hazard:NONE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:FLUSH TO SEWER WITH LARGE AMOUNMTS OF WATER.

Neutralizing Agent:NOT RELEVANT

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES.

Other Precautions:USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED.

Ventilation:GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES/HR)

SHOULD BE USED. VENTILATION RATES SHOULD BE MATCHED TO CONDITIONS

Protective Gloves:IMPERV

IOUS GLOVES SHOULD BE WORN.

Eye Protection:WEAR SAFETY GLASSES/SIDE SHIELD, GOGGLES

Other Protective Equipment:EYE BATH, SAFETY SHOWER, WASHING FACILITIES.

Work Hygienic Practices:OBSERVE GOOD INDUSTRIAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. WASH THOROUGHLY BEFORE EATING, DRINKING/SMOKING.

Supplemental Safety and Health

ITEM HAS SEVEN PARTS IN THE KIT.THIS PART IS EKTAPRINT BLEACH-FIX, PART A WHICH MAY BE MARKED WITH CAT #186 5849. BUT CAT #186 2176 IS FOR THE KIT; THIS N

SN IS DUPLICATE OF 6750-01-068-0727, SAME CAT NO;

YIELDS 1 GAL & SOLUTION #; MSDS OF CAT # 186 5849 IS USED FOR KIT.

SOLUTION NUMBER= 4354; KEY1:C3

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F,>100C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.33

pH:5.3

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR,COLORLESS LIQUID; SULFUR DIOXIDE ODOR

Percent Volatiles by Volume:45%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

BASES, SODIUM HYPOCHLORITE, STRONG ACIDS, STRONG OXIDIZING AGENTS. CONTACT WITH BASE LIBERATES FLAMMABLE MATERIALS.

Stability Condition to Avoid:NONE.

Hazardous Decomposition Products:AMMONIA, CHLORAMINE, NITROGEN OXIDES, SULFUR DIOXIDES.

===== Disposal Considerations =====

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL REGULATIONS.

Dis

claimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.