View NSN Online: https://aerobasegroup.kr/nsn/3439-01-233-7463

ALPHA METALS -- ENERGIZED ROSIN CORE SOLDER -- 3439-01-233-7463

Product ID: ENERGIZED ROSIN CORE SOLDER MSDS Date:05/02/1989 FSC:3439 NIIN:01-233-7463 MSDS Number: BGRBX === Responsible Party === Company Name: ALPHA METALS Address:600 ROUTE 440 City: JERSEY CITY State:NJ ZIP:07304 Country:US Info Phone Num:201-434-6778 Emergency Phone Num:201-434-6778 CAGE:96613 === Contractor Identification === Company Name: FRYS METALS INC (FORMER ALPHA METALS) Address:600 ROUTE 440 Box:City:JERSEY CITY State:NJ ZIP:07304 Country:US Phone:201-434-6778 CAGE:96613 

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Fraction by Wt: 35.53% Other REC Limits:NONE SPECIFIED OSHA PEL:0.05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:TIN CAS:7440-31-5 RT ECS #:XP7320000 Fraction by Wt: 63.5% Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9192

Ingred Name:SILVER (SARA III) CAS:7440-22-4 RTECS #:VW3500000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH CAS:7440-69-9 RTECS #:EB2600000 Fraction by Wt: 0.25% Other REC Limits:NONE SPECIFIED

Ingred Name:ANTIMONY (SARA III) CAS:7440-36-0 RTECS #:CC4025000 Fraction by Wt: 0.50% Other REC Limits:N ONE SPECIFIED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG SB/M3; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:INDIUM CAS:7440-74-6 RTECS #:NL1050000 Other REC Limits:NONE SPECIFIED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3; 9192

Ingred Name:ROSIN ACID CAS:8050-09-7 Other REC Limits:NONE SPECIFIED

LD50 LC50 Mixture:ORAL LD50 (RATS) > 5000 MG/KG (ROSIN) Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES Reports of Car cinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MOLTEN SOLDER ALLOYS DO NOT PRODUCE SIGNIFICANT LEAD FUME BELOW 700F. EXPOSURE TO HIGH LEVELS OF AIRBORNE OR INGESTED LEAD MAY PRODUCE SYMPTOMS OF ANEMIA, INSOMINIA, WEAKNESS, CONSTIPATION, NAUSEA & ABDOMINAL PAIN. PROLONGED EXPOSURE MAY RESULT IN KIDNEY & NERVOUS SYSTEM INVOLVEMENT. PREGNANT WOMEN SHOULD AVOID LEAD.
Explanation of Carcinogenicity:NOT LISTED BY NTP, IARC OR OSHA AS A

Eff

CARCINOGEN.

ects of Overexposure:LOSS OF APPETITE, METALLIC TASTE IN THE MOUTH, ANXIETY, CONSTIPATION, NAUSEA, PALLOR, EXCESSIVE TIREDNESS, WEAKNESS, INSOMNIA, HEADACHE, NERVOUS IRRITABILITY, MUSCLE AND JOINT SORENESS, TREMORS, DIZZI NESS, AND ABDOMINAL PAIN. WHEN HEATED, FUMES MAY CAUSE EYE, SKIN & RESPIRATORY TRACT IRRITATION. SOLDER CAN CAUSE BURNS.

Medical Cond Aggravated by Exposure:DISEASES OF THE BLOOD-FORMING, NERVOUS, URINARY, RESPIRATORY AND REPRODUCTIVE SYSTEMS. EXPOSURE T O

LEAD MAY RESULT IN INJURY TO A DEVELOPING FETUS.

First Aid:IF A PERSON BREATHES IN A LARGE AMOUNT OF ROSIN FUME, REMOVE FROM EXPOSURE. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN AND CALL A PHYSICIAN. IF LEAD HAS BEEN INGESTED, IMMEDIATELY CALL A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. FOR EYE BURNS, FLUSH IMMEDIATELY WITH COOL WATER AND OBTAIN MEDICAL AID. FOR SKIN BURNS,

COOL WITH WATER AND OBTAIN MEDICAL AID.

Flash Point:NONE

 Autoignition Temp:Autoignition Temp Text:NONE
 Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.
 Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.
 Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HIGHLY TOXIC FUMES FROM LEAD.

=========== Accidental Relea

se Measures ===============

Spill Release Procedures: SOLID AT ROOM TEMPERATURE. IF IN MOLTEN STATE, ALLOW TO COOL AND SOLIDIFY AND THEN SCRAPE UP. VACUUM UP SMALL PARTICLES. NEVER USE ANY METHOD WHICH WILL GENERATE DUST.

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR LEAD, IF EXPOSURES EXCEED THE OSHA LIMIT. 0.03 MG/M3 - HALF MASK; 2.5 MG/M3 - FULL FACE MASK; 50 MG/M3 - SELF-SUSTAINED RESPIRATORY SUIT. Ventilation:USE ENOUGH VENTILATION (GENERAL/LOCAL) TO KEEP THE FUMES FROM THE WORKERS BREATHING ZONE & BELOW PEL. HEPA FILTERS REQD. Protective Gloves:LEATHER GLOVES Eye Protection:SAFETY GOGGLES OR FACE SHIELD Other Protective Equipment:AS REQUIRED TO AVOID CONTACT. Work Hygienic Practices:WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDER CONTAMINATIED CLOTHING BEFORE REUSE. FOLLOW GOOD HYGIENIC PRACTICES. Supplemental Safety and Health EXPOSURE TO LEAD IS REGULATED BY OSHA 1910.1025

HCC:T4 Vapor Pres:0 Solubility in Water:NEGLIGIBLE Appearance and Odor:SILVER-GRAY METAL WIRE, ODORL ESS, 0.020 INCHES DIAMETER. Percent Volatiles by Volume:0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS AND STRONG MINERAL ACIDS. Stability Condition to Avoid:NONE Hazardous Decomposition Products:THE SMOKE FROM A SOLDERING OPERATION MAY INCLUDE CARBON MONOXIDE, ABIETIC ACID, ALIPHATIC ALDEHYDES & DITERPENE ACIDS.

Waste Dispo

sal Methods:RECLAIM ALLOY OR DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE & LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional adv ice to verify and assume responsibility for the suitability of this information to their

assume responsibility for the suitability of this information to their particular situation.