

FISKE BROTHERS REFINING CO. -- LUBRIPLATE FMO-AW SERIES LUBE OILS -- 9150-01-237-7467

===== Product Identification =====

Product ID:LUBRIPLATE FMO-AW SERIES LUBE OILS

MSDS Date:10/01/1988

FSC:9150

NIIN:01-237-7467

MSDS Number: BGRDD

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO.

Address:129 LOCKWOOD ST.

City:NEWARK

State:NJ

ZIP:07105

Info Phone Num:201-589-9150

Emergency Phone

Num:201-589-9150

Preparer's Name:ROBERT J. SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:

804-355-8041
CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:VIRGIN PETROLEUM LUBRICATING OIL
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3

Ingred Name:ADDITIVES

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PROLONGED/REPEATED CONTACT MAY PRODUCE

IRRITATION. PRODUCT HAS LOW ORDER ORAL TOXICITY & VERY LOW VAPOR PRESSURE MAKING INHALATION & INGESTION HAZARDS LOW. HOWEVER ASPIRATION OF LIQUID INTO LUNG MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Explanation of Carcinogenicity:THIS COMPOUND CONTAINS NO INGREDIENTS AT CONCENTRATIONS OF 0.1% OR GREATER THAT ARE CARCINOGENS OR SUSPECT CARCINOGENS.

Effects of Overexposure:EYE/SKIN:POSSIBLE IRRITATION. INHALED: UNLIKELY. INGESTED:G/I IRRITATION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:REMOVE CONTAMINATED CLOTHING,WASH WITH SOAP & WATER. INHALED:(PRODUCT MISTED OR VAPORIZED BY ELEVATED TEMPERATURES) REMOVE FROM EXPOSURE,GET MEDICAL ATTENTION. INGESTED:DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:COC
Flash Point:>34

0F/171C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE,WATER FOG

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:KEEP OUT OF SEWERS & WATER COURSES. RECOVER LIQUID. ABSORB REMAINDER WITH SUITABLE MATERIAL. CLEAN AREA WITH PETROLEUM SOLVENT.

Neutralizing

Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE TIGHTLY CLOSED. KEEP AWAY FROM IGNITION SOURCES & STRONG OXIDIZING AGENTS.

Other Precautions:DO NOT CUT,WELD,ETC.,ON "EMPTY" CONTAINERS. EXPLOSION HAZARD. - LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED. WEAR NIOSH RESPIRATOR FOR

OIL MIST OR ORGANIC VAPORS WHEN EXPOSURE DICTATES.

Ventilation:NORMAL ROOM VENTILATION WITH LOCAL EXHAUST TO REMOVE ANY VAPORS OR MIST.

Protective Gloves:OIL RESISTANT

Eye Protection:SAFETY GLASSES,SPLASH GOGGLES

Other Protective Equipment:OIL RESISTANT APRON AND/OR CLOTHING IF TASK INCLUDES SPLASH RISK.

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

=====

HCC:V6

Boiling Pt:B.P. Text:>550F/288C

Vapor Pres:5

Spec Gravity:0.86-0.89

Evaporation Rate & Reference: