View NSN Online: https://aerobasegroup.com/nsn/6850-01-263-8224

MAGNAFLUX CORPORATION -- ZE-3 ZYGLO EMULSIFIER -- 6850-01-263-8224

========= Product Identification ============

Product ID:ZE-3 ZYGLO EMULSIFIER

MSDS Date:06/22/1989

FSC:6850

NIIN:01-263-8224

Kit Part:Y

MSDS Number: BGRPT === Responsible Party ===

Company Name: MAGNAFLUX CORPORATION

Address:7300 W LAWRENCE AVE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:708-867-8000 Emergency Phone Num:70

8-867-8000

Preparer's Name: BRUCE C. GRAHAM

CAGE:37676

=== Contractor Identification ===

Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL ZIP:60025 Country:US

Phone:847-657-5300/

CAGE:37676

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000 Fraction by Wt: 50.0% OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name: "NOT HA

Fraction by Wt: 50% Other REC Limits:NONE ESTABLISHED
============ Hazards Identification ============
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE:MAY IRRITATE EYES.SEE OVEREXPOSURE SYMPTOMS. Effects of Overexposure:INHALATION:NOT LISTED BY MANUFACTURER.HOWEVER,FINE SPRAY/MIST MAY CAUSE IRRITATION TO BREATHING PASSAGES; EYES:LIQUID/MIST CAUS ES IRRITATION; SKIN:PROLONGED OR REPEATED CONTACT CAUSES IRRITATION BY DI SSOLVING SKIN OILS; INGESTION:NOT NOTEDBY MANUFACTURER. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY THE MANUFACTURER.
======================================
First Aid:INHALATION:REMOVE TO FRESH AIR; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF PROMPTLY WITH SOAP AND WATER.USE SOOTHING LOTION.GET MEDICAL HELP IF IRRITATION PERSISTS; EYES:IMMEDIATELY RINSE EYES WITH COP IOUS AMOUNT OF WATER.GET MEDICAL ASSISTANCE IF IRRITATION PERSISTS; INGESTION:NOT STATED BY MANUFACTURER.GET MEDICAL ATTENTION IF INGESTED.
======================================
Flash Point Method:PMCC Flash Point:325F/163C Extinguishing Media:CARBON DIOXIDE,FOAM. Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.
==== ======== Accidental Release Measures ============
Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.
=========== Handling and Storage ============
Handling and Storage Precautions:STORE AWAY FROM HEAY SOURCES IN WELL VENTILATE

ZARDOUS" INGREDIENTS

D AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions: DO NOT BREATHE VAPORS. DO NOT SMOKE WHILE USING. DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USE NIOSH APPROVED RESPIRATORS FOR CONFINED AREAS. Ventilation: GENERAL ROOM VENTILATION TO KEEP BELOW TLV LIMITS. Protective Gloves: USE NITRILE RUBBER GLOVES IF NEEDED. ection:FULL GOGGLES/SAFETY GLASSES W/SIDESHIELD Other Protective Equipment: NOT KNOWN. Work Hygienic Practices: WASH OFF PROMPTLY WITH WATER. AVOID SKIN CONTACT. Supplemental Safety and Health NSN IS FOR A 2 PARTS SET OF MIL-I-25135D I/A/W QPL-25135-15,THE SET UNDER TYPE I,METHOD B,LEVEL 4 MAY CONSIST OF ZL-30B,ZL-37 OR ZL-38 PENETRANT & ZE-3 OR ZE-4B EMULSIFIER. THIS ENTRY DESCRIBES ZE-3; T HE QPL ALSO INDICATES THAT THIS PRODUCTCAN GO IN SEVERAL KITS UNDER TYPE I,METH A,B,C,D & LEVEL 1,2,3,4;KEY1:N1. ========= Physical/Chemical Properties =========== HCC:N1 Boiling Pt:B.P. Text:>450F/>232C Vapor Pres:0.3@100F Vapor Density:>1.0 Spec Gravity:0.75

0.8:Hq Solubility in Water: NEGLIGIBLE Appearance and Odor: VISCOUS PINK LIQUID.

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES NONE STATED BY MANUFACTURER. Stability Condition to Avoid: HEAT, HIGH TEMPERATURES. Hazardous Decomposition Products:E

MITS OXIDES OF CARBON IF BURNING.

======= Disposal Considerations ============

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORITIES PROHIBIT DUMPING RINSINGS DOWN THE SEWER,P URIFY RINSINGS WITH MAGNAFLUX WASTEWATER TREATMENT

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.