View NSN Online: https://aerobasegroup.kr/nsn/6850-01-263-8225

MAGNAFLUX CORPORATION -- ZL-30B ZYGLO PENETRANT -- 6850-01-263-8225

Product ID:ZL-30B ZYGLO PENETRANT MSDS Date:11/19/1986 FSC:6850 NIIN:01-263-8225 Kit Part:Y MSDS Number: BGRPW === Responsible Party === **Company Name: MAGNAFLUX CORPORATION** Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656-3504 Country:US Info Phone Num:312-867-8000 **Emergency Phone Nu** m:312-867-8000 Preparer's Name: BRUCE C. GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:LUBRICATING OIL(PETROLEUM),CLAY TREATED (MINERAL OIL-CLAY TREATED) CAS:64742-50-3 Fraction by Wt: 10.0%

Ingred Name:KEROSENE CAS:8008-20-6 RTECS #:OA5500000 Fra ction by Wt: 05.0% ACGIH TLV:100MG/CUM

Ingred Name:DISTILATES(PETROLEUM),CATALYTIC REFORMER FRACTIONATER RESIDUE,LOW BOILING CAS:68477-31-6 Fraction by Wt: 30.0% OSHA PEL:5MG/CUM FOR OIL MIST ACGIH TLV:5MG/CUM FOR OIL MIST

Ingred Name:UNIDENTIFIED COMPONENTS Fraction by Wt: 55.0%

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO Health Hazards Acute and Chronic:IRRITATES EYES. Effects of Overexposure:INHALATION:CAUS ES DIZZINESS,DROWSINESS,NAUSEA; SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPORS/LIQUID CAUSES IRRITATION.

Medical Cond Aggravated by Exposure:NOT KNOWN.

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN; EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS A MOUNT OF RUNNING WATER.AND GET MEDICAL ATTENTION.

Flash Point Method:PMCC Flash Point:>200F/>93C Extinguishing Media:CARBON DIOXIDE,FOAM. Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY. Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY CAUSE TOXIC GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

Spill Release Procedures:REMOVE

IGNITION SOURCES.SM QTY:WIPE UP OR MOP UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE TANKS.

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP CONTAINERS TIGHTLY CLOSED.

Other Pre

cautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: WEAR RESPIRATOR WITH CHEMICAL CARTRIDGE IF USING IN POORLY VENTILATED AREA.AVOID BREATHING VAPOR OR SPRAY MIST. Ventilation: GENERAL VENTILATION TO KEEP BELOW LIMITS OF TLV. Protective Gloves: NITRILE GLOVES IF USING FREQUENTLY. Eye Protection: FULL GOGGLES WHEN SPRAYING OR P OURING. Other Protective Equipment: USE IN SPRAY BOOTH OR WHERE VENTILATION IS ADEQUATE TO CARRY VAPORS & OVERSPRAY FROM OCCUPIED AREAS. Work Hygienic Practices: LAUNDER CONTAMINATED CLOTHES BEFORE REUSE. WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health ITEM IS A 2 PARTS SET; UNDER QPL-25135-15 OF MIL-I-25135D, THE KIT OF TYPE I,METHOD B,LEVEL 4 MAY CONSIST OF ZL-30B,ZL-37,OR ZL-38 PENETRANT AND ZE-3 OR ZE-4B EMULSIFIER; SEE PNI D & E FOR EMULSIFIER DAT A;KEY1:N1;THIS ENTRY DESCRIBES ZL-30B;SEE PNI B & C FOR OTHER QUALIFIED PENETRANTS FOR THIS NSN.

HCC:N1 Boiling Pt:B.P. Text:410F/210C Vapor Pres:1.0 Spec Gravity:0.96 Solubility in Water:NEGLIGIBLE Appearance and Odor:GREEN OILY LIQUID. Percent Volatiles by Volume:5%

Stability Indicator/Materials to Avoid:YES NONE KNOWN. Stability Condition to Avoid:HEAT,HIGH TEMPER

## ATURES.

Hazardous Decomposition Products: EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D001 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Unit

ed States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.