

MAGNAFLUX CORPORATION -- ZL-55 ZYGLO WATER WASHABLE PENETRNT -- 6850-01-263-9774

=====
Product Identification
=====

Product ID:ZL-55 ZYGLO WATER WASHABLE PENETRNT

MSDS Date:11/13/1985

FSC:6850

NIIN:01-263-9774

MSDS Number: BGRSK

=== Responsible Party ===

Company Name:MAGNAFLUX CORPORATION

Address:7300 W. LAWRENCE AVENUE

City:CHICAGO

State:IL

ZIP:60656-3504

Country:US

Info Phone Num:708-867-8000

Em

ergency Phone Num:708-867-8000

Preparer's Name:BRUCE C. GRAHAM, CH. CHEM

CAGE:37676

=== Contractor Identification ===

Company Name:ILLINOIS TOOL WORKS INC MAGNAFLUX DIV

Address:3624 WEST LAKE AVENUE

Box:City:GLENVIEW

State:IL

ZIP:60025

Country:US

Phone:847-657-5300/

CAGE:37676

=====
Composition/Information on Ingredients
=====

Ingred Name:SECONDARY ETHOXYLATED FATTY ALCOHOLS

CAS:68131-40-8

RTECS #:WZ5200000

Fraction by Wt: 50.0%

Ingred Name:UNIDENTIFIED COMPONENTS

Fraction b

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:IRRITATES EYES ON LIQUID/VAPOR
CONTACT.

Effects of Overexposure:INHALATION:CAUSES DIZZINESS,DROWSINESS,NAUSEA;
SKIN:LIQUID IRRITATES BY DISSOLVING SKIN OIL; EYES:VAPOR/LIQUID
CAUSES IRRITATION; INGESTION:MANUFACTURER DIDN'T LIST.

Medical Cond Aggravated by Exposure:NOT KNOWN.

=====
First Aid Measur
es
=====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT,GIVE
OXYGEN; SKIN:REMOVE CONTAMINATED CLOTHES.WASH OFF WITH FLOWING
WATER.USE SOOTHING LOTION.IF IRRITATION PERSISTS,GET MEDICAL ATTN;
EYES:IMM EDIATELY RINSE/FLUSH WITH COPIOUS AMOUNT OF RUNNING
WATER,AND GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:PMCC

Flash Point:>250F/121C

Extinguishing Media:CARBON DIOXIDE,FOAM.

Fire Fighting Procedures:KEEP CONTAINERS COOL WITH WATER SPRAY.DO NOT
SPRAY WATER ON BURNING ZL-55.

Unusual Fire/Explosion Hazard:WHEN INVOLVE IN COMBUSTION,MAY EMIT TOXIC
GASES AT OR ABOVE DECOMPOSITION TEMPERATURE.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES.SM QTY:WIPE UP OR MOP
UP BUT DO NOT BREATHE VAPORS.PLACE RAGS IN CLOSED DRUMS; LG
QTY:WEAR PERSONAL SAFETY EQUIPMENTS.DIKE AREA FAR AHEAD.ABSORB

LIQUID WITH COMMERCIAL ABSORBEN T.TRANSFER WASTE MATL IN SALVAGE
TANKS.

Neutralizing Agent:NOT KNOWN.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AWAY FROM HEAT SOURCES IN WELL
VENTILATED AREA.AVOID AGAINST PHYSICAL DAMAGE TO CONTAINERS.KEEP
CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT BREATHE VAPORS.DO NOT SMOKE WHILE USING.DO NOT
HEAT ABOVE 130F(54C).AVOID FREQUENT OR PROLONGED SKIN CONTACT.

=====

Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR FOR CONFINED AREAS.

Ventilation:GENERAL ROOM VENTILATION TO KEEP BELOW TLV LIMITS.

Protective Gloves:USE NITRILE RUBBER GLOVES IF NEEDED.

Eye Protection:FULL GOGGLES/SAFETY GLASSES W/SIDESHIELD

Other Protective Equipment:NOT KNOWN.

Work Hygienic Practices:WASH OFF PROMPTLY WITH WATER.AVOID SKIN CONTACT.

Supplemental Safety and Health

NSN OF MIL-I-25135D,TYPE I,METHOD C,LEVEL 3;PER

QPL-25135,MAGNAFLUX

CORP MAY SUPPLY ONE OF THE FOLLOWING PENETRANTS FOR TYPE I,METHOD C,LEVEL 3 NSN:ZL-22D,ZL-27A,ZL-37,ZL-54A,ZL-55 OR ZL-66A;THIS ENTRY DESCRIBES ZL-55;PRODUCT NOT AVAILABLE IN AEROSOL CANS;SEE OTHER P/N IND OF THIS NSN FOR OTHER QUALIFIED ITEMS.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:400F/204C

Vapor Pres:1.0

Spec Gravity:1.01

Evaporation Rate & Reference:NOT KNOWN

Solubility in Water:NEGLIGIBLE(EMULSIFY)

Appearance and Odor:GREEN OILY LIQUID.

Percent Volatiles by Volume:5.0%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NOT KNOWN TO MFR.

Stability Condition to Avoid:HEAT,HIGH TEMPERATURES.

Hazardous Decomposition Products:EMITS OXIDES OF CARBON AND NITROGEN ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR DISPOSE OF AS EPA HAZARDOUS WASTE D00

1 (IGNITABLE WASTE),IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL,STATE,LOCAL REGULATIONS;IF LOCAL AUTHORITIES DO NOT ALLOW
DUMPING RINSINGS DOWN THE SEW ER,PURIFY RINSINGS WITH MAGNFLUX
TREATMENT SYSTM

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims
all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.