

MET-L-CHEK COMPANY -- E-59 REMOVER -- 6850-00-160-8481

===== Product Identification =====

Product ID:E-59 REMOVER

MSDS Date:10/24/1986

FSC:6850

NIIN:00-160-8481

MSDS Number: BGSZP

=== Responsible Party ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA

ZIP:90404-3723

Country:US

Info Phone Num:213-450-1111

Emergency Phone Num:213-450-1111

CAGE:98733

=== Contr

actor Identification ===

Company Name:MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA

ZIP:90404

Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT NAPHTHA (PETROLEUM MEDIUM ALIPHATIC

CAS:64742-88-7

OSHA PEL:500PPM

ACGIH TLV:100PPM

Ingred Name:SOLVENT NAPHTHA (PETROLEUM LIGHT AROMATIC

CAS:64742-95-6

OSHA PEL:500PPM

ACGIH TLV:100PPM

Ingred Name:ISOBUTANE/PROPANE MIXTURE

(AS PROPELLANT)
OSHA PEL:1000PPM (PROPANE)
ACGIH TLV:ASPHYXIANTS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:EYES: LIQUID CONTACT MAY CAUSE IRRITATION.
SKIN: CAUSES SLIGHT IRRITATION. INHALATION: VAPOR OR OIL MIST MAY
CAUSE MILD IRRITATION OF UPPER RESPIRATORY TRACT. INGESTION: MAY
RESULT IN VOMITING. ASPIRATION MUST BE AVOID
ED.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN AND RESPIRATORY
DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH RUNNING WATER FOR AT LEAST 15 MINUTES. GET
MEDICAL HELP IF IRRITATION PERSISTS. SKIN:FLUSH WITH WATER. WASH
WITH SOAP AND WATER. INHALATION:REMOVE TO FRESH AIR, PROVIDE OXYGEN
IF BREATHING IS DIFFICULT. INGESTION:DO NOT INDUCE VOMITING. GET
MEDICAL AS
SISTANCE FOR ANY OF HEALTH PROBLEMS.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:140F,60C
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:WATER FOG,DRY CHEMICAL,CARBON DIOXIDE OR FOAM; DO
NOT USE DIRECT STREAM OF WATER ON THE FIRE.
Fire Fighting Procedures:IN CONFINED AREA,DO NOT ENTER WITHOUT A FULL
BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED
SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CONTAINERS MAY BURST AND/OR RUPTURE IN
INTENSE HEAT OF FIRE. PER MANUFACTURER,PRODUCT MAY IGNITE IN AIR
WHEN EXPOSED TO FLAME OR PREHEATED.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES.WEAR APPROPRIATE
PROTECTIVE CLOTHING AND RESPIRATORS.SOAK UP WITH ABSORBENT.PLACE
WASTE IN SEALED CONTAINERS.FLUSH WITH WATER.LARGE SPILL:DIKE LIQUID
& PUMP INTO SALVAGE TANK.ABSORB RESIDUE WITH COMM ABSORBENT &

PUT
IN DRUM

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM SOURCES OF
HEAT/IGNITION.STORE IN COOL,DRY & VENTILATED AREA.DO NOT STORE NEAR
OXIDIZING MATERIAL;AVOID PHYSICAL DAMAGE TO CONTAINERS.

Other Precautions:MINIMIZE SKIN CONTACT.AVOID BREATHING VAPORS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NOT NEEDED IN NORMAL CONDITIONS OR WHEN
VAPORS/MIST CONCENTRATIONS ARE BELOW TLV/PEL LIMITS. WEAR NIOSH
APPROVED ORGANIC TYPE RESPIRATOR IN ABSENCE OF PROPER ENVIRONMENTAL
CONTROL.

Ventilation:LOCAL EXHAUST OR MECHANICAL(GENERAL) TO MAINTAIN TLV OR
BELOW TLV LIMITS.

Protective Gloves:CHEMICAL RESISTANT

Eye Protection:SAFETY GLASSES OR SPLASH-PROOF GOGGLES

Other Protective Equipment:CHEMICAL RESISTANT APRON TO PREVENT
CLOTHING/SKIN CONTACT.

Work Hygienic Practices:WASH HANDS WITH SOAP & WATER BEFORE
EATING,SMOKING OR USING TOILET FACILITIES;DO NOT EAT/DRINK IN VAPOR
CONTAMINATED AREA.

Supplemental Safety and Health

ITEM IS SINGLE UNIT FOR MIL-I-25135,REV D,QPL-25135-15.

=====
Physical/Chemical Properties
=====

HCC:V3

Boiling Pt:B.P. Text:368F,187C

Vapor Pres: