View NSN Online: https://aerobasegroup.kr/nsn/6850-01-268-8788

MET-L-CHEK COMPANY -- E-57 EMULSIFIER -- 6850-01-268-8788

============ Product Identification =========================

Product ID:E-57 EMULSIFIER

MSDS Date:01/01/1997

FSC:6850

NIIN:01-268-8788

Kit Part:Y

MSDS Number: BGTLJ === Responsible Party ===

Company Name: MET-L-CHEK COMPANY

Address:1639 EUCLID STREET

City:SANTA MONICA

State:CA ZIP:90404 Country:US

Info Phone Num:310-450-1111

Emergency Phone Num:310-450-1111/800-424-9

300(CHEMTREC) CAGE:98733

=== Contractor Identification ===

Company Name: MET-L-CHEK COMPANY

Address:1639 EUCLID ST

Box:00000

City:SANTA MONICA

State:CA ZIP:90404 Country:US

Phone:310-450-1111/FAX 310452-4046

CAGE:98733

======= Composition/Information on Ingredients ========

Ingred Name:PETROLEUM HYDROCARBON/MINERAL OIL, PETROLEUM DISTILLATE, SOLVENT REFINED (SEVERE), HEAVY NAPHTHENIC

CAS:64741-96-4 RTECS #:PY8040001

Other REC Limits: NONE RECOMMENDED

OSHA PEL:5 MG/M3 AS OIL MIST

ACGIH TLV:5 MG/M3 AS OIL MIST ========== Hazards Identification ================ LD50 LC50 Mixture:LD50 (ORAL, RAT) IS NOT KNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:TARGET ORGANS: EYE, SKIN, RESPIRATORY & GI TRACTS. ACUTE- EYE CONTACT IS NON-IRRITATING. MAY CAUSE SLIGHT SKIN IRRITATION. VAPORS OR OIL MISTS MAY CAUSE RESPIRATORY TRACT IRRITATION, INGESTION MAY RES ULT IN VOMITING. ASPIRATION HAZARD. CHRONIC- UNKNOWN. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: IRRITATION, NAUSEA, VOMITING Medical Cond Aggravated by Exposure: PRE-EXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGAVATED BY EXPOSURE TO THIS PRODUCT. First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: MOVE TO FRESH AIR. PROVIDE OXYGEN IF NEEDED. EYES: FLUSH WITH WATER FOR 15 **MINUTES** , HOLDING EYELIDS OPEN. SKIN: FLUSH WITH WATER & WASH SKIN WITH SOAP & WATER. ORAL: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION. IF VOMITING OCCURS, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION. Flash Point Method: PMCC Flash Point:>200F,>93C Extinguishing Media: WATER FOG, DRY CHEMICAL/CARBON DIOXIDE. DON'T USE DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED. Fire Fighting Procedures: IN CONFIN ED AREA, DO NOT ENTER WITHOUT A FULL BUNKER GEAR INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:NONE ======== Accidental Release Measures ============

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. VENTILATE AREA. STOP LEAK IF POSSIBLE. USE PUMP TO TRANSFER LARGE SPILLS TO CONTAINER. REMAINING LIQUID/SMALL SPILLS CAN BE TAKEN UP ON SAND, CLAY, EARTH & SHOVELD INTO CONT AINERS. PREVENT RU

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATION RECOMMENDED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shou

Id seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.