

FENWAL,INC. -- 39-080055-510 PART A (EPOXY RESIN) -- 8040-00-078-5073

=====
Product Identification
=====

Product ID:39-080055-510 PART A (EPOXY RESIN)

MSDS Date:09/01/1988

FSC:8040

NIIN:00-078-5073

Kit Part:Y

MSDS Number: BGVZH

=== Responsible Party ===

Company Name:FENWAL,INC.

Address:400 MAIN ST.

City:ASHLAND

State:MA

ZIP:01721

Info Phone Num:508-881-2000

Emergency Phone Num:508-881-2000

CAGE:J

O994

=== Contractor Identification ===

Company Name:FENWAL,INC.

Address:400 MAIN ST.

Box:City:ASHLAND

State:MA

ZIP:01721

Phone:508-881-2000

CAGE:JO994

Company Name:FENWAY SAFETY SYSTEMS INC

Address:700 NICKERSON RD

Box:City:MARLBOROUGH

State:MA

ZIP:01752

Country:US

CAGE:73168

=====
Composition/Information on Ingredients
=====

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by Wt: 35-60%

OSHA PEL:2 MG/M3 RDUST

ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:EPOXY RESIN

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PRODUCT HAS HAZARD ONLY IF MISTED OR
DUSTED, BOTH UNLIKELY OCCURANCES. CHRONIC INHALATION OF TALC MAY
CAUSE PNEUMONOCONISIS.

Effects of Overexposure:INHALED(AS DUST):RESPIRATORY
IRRITATION,COUGHING. INGESTION:NO REPORTED HAZARD. SKIN:NO REPORTED
HAZARD, EYE:TEMPORARY DISCOMFORT,AS WITH ANY FOREIGN MATT
ER.

Medical Cond Aggravated by Exposure:NONE

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER.IF DISCOMFORT CONTINUES,GET MEDICAL
CARE. SKIN:WASH WITH SOAP & WATER. INHALED:REMOVE TO FRESH AIR. IF
BREATHING DIFFICULTY DEVELOPS,GIVE OXYGEN AND GET MEDICAL CARE.
INGESTED:NO TREATMENT NECESSARY.

=====
===== Fire Fighting Measures =====

Flash Point:480F/249C

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL
,FOAM,WATER FOG.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS.
PRODUCT WILL NOT BURN UNLESS PRE-HEATED.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH INERT MATERIAL. WIPE UP CLEAN
RESIDUE WITH SOAP & WATER.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL VENTILATED

A

REA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE EXPECTED TO BE NECESSARY. REQUIRED ONLY IF PRODUCT IS HEATED.

Ventilation:NORMAL ROOM VENTILATION.

Protective Gloves:RUBBER,PLASTIC, OTHER IMPERVIOUS

Eye Protection:SAFETY GLASSES.OR SPLASH GOGGLES

Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT.

Supplemental Safety and Health

WHEN USING BOTH PARTS OF THE KIT,SEE P/N IND B FOR MSDS AS IT IS THE

HAZARDOUS.PART OF THE 2 PART KIT *MSDS INDEX 3158*.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>500/260C

Vapor Pres:NIL

Spec Gravity:1.57

Solubility in Water:INSOLUBLE

Appearance and Odor:WHITE HIGH VISCOCITY LIQUID,MILD ODOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AMINES(UNCONTROLLED),STRONG OXIDIZERS,MINERAL ACIDS.

Stability Condition

to Avoid:NONE REPORTED

Hazardous Decomposition Products:CARBON MONOXIDE,ALDEHYDES,ACIDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL,REGULATIONS.
MFR SUGGESTS INCINERATION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warran

ts this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.